




CHEMICAL FREE ULTRAVIOLET DISINFECTION

SPDI UV Total-Cure 36" Conveyor System with Dual UVA Curing Irradiators



SKU: 301153

PRODUCT HIGHLIGHTS

Improve your curing speed and efficiency while maintaining cure quality and consistency with our speed adjustable high-output UV Curing Conveyor.

- Available with - Mercury (365 nm). - Iron-Doped (390 nm) - Gallium (420 nm) curing lamps.
- Available in curing sizes from 12" to 54".
- Belt speed adjustable from 0.1 to 40 feet per minute.
- Industry leading 2 year warranty.
- Heavy duty industrial steel construction.
- Adjustable entry and exit allow you to cure items of varying shapes and sizes.
- High output curing lamps ensure proper through-cure.

TECHNICAL SPECIFICATIONS

INFO	
DIMENSIONS:	60"(L) X 36" (W)
BELT HEIGHT FROM FLOOR:	34 IN.
AVAILABLE LAMPS	MERCURY (365 NM), IRON-DOPED (390 NM), GALLIUM (420 NM)
DIRECTION:	LEFT TO RIGHT FROM CONTROL
UV WATTAGE:	16,000 WATTS (TWO X 8,000 WATT LAMPS)
OPENING HEIGHT:	12 IN.
FAN:	500 WATT COOLING FAN
BELT SPEED:	0.1 – 40 FT/MIN

SYSTEM ARCHITECTURE

Conveyor Speed	15 ft/min		20 ft/min		30 ft/min		40 ft/min	
Intensity/Dosage	Mw/cm2	mJ/cm2	Mw/cm2	mJ/cm2	Mw/cm2	mJ/cm2	Mw/cm2	mJ/cm2
UVA	448	1150	437	691	437	532	433	415
UVB	402	1043	397	632	395	488	398	381
UVC	113	299	112	181	111	140	111	109
UVV	356	901	351	544	348	418	346	326



This document is copyright @ August 13, 2020 CureUV. All rights reserved. This document is provided for information purposes only. Contents are subject to change without notice. It is not warranted to be error-free. Nor subject to any other warranties or conditions including implied warranties and conditions of merchantability or fitness for a particular purpose.

cureuv.com

YOUR UV LIGHT EXPERTS

Phone: (800) 977-7292

Address: 2855 S. Congress Ave. Ste. C, Delray Beach, FL, 33445

Web store: www.cureUV.com