SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION Product Name: POLYBAC #1618 AND COLORS - PART B Company: POLYGEM INC.
PO Box 609
West Chicago, Illinois 60185 Telephone: 630-231-5600
630-231-5604 (Fax Line) Emergency Telephone Number: 1-800-535-5053
01-352-323-3444 USA
International

Section 2 - HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification according to the Regulation (EC) No. 1272/2008

Acute Dermal Toxicity Category 4

Acute Oral Toxicity Category 4

Skin Sensitization Category 1

Skin Corrosion/Irritation Category 1B

Chronic Aquatic Toxicity Category 2

Classification according to the Regulation Directive 199/45/EC: [Xn] Harmful, [C] Corrosive, [N] Dangerous to the Environment Information Concerning particular hazards for human and environment:

Product Description: This product is grey heavy paste with a sweet amine odor

Health Hazards: Corrosive, Severe eye irritant; Respiratory Irritant, may cause skin sensitization.

Flamability Hazards: This product is flammable above it's fashpoint of 380F (195 C)

Reactivity Hazards: None known.

Environmental Hazards: The environmental effects of this product have not been investigated; however it is not expected to cause significant adverse effects.

Emergency Considerations: Emergency responders must wear proper personal protective equipment (and have appropriate fire suppression equipment) suitable for the situation to which they are responding.

Classification system:

This classification is according to the latest editions of the EU-lists, and extended by company and literature data.

2.2 Label elements

Labeling according to Regulation (EC) no. 1272/2008:

Hazard Pictograms:



Signal Word: Danger Hazard-determining component of labelling: Diethylenetriamine Hazard Statements: H302: Harmful is swallowed H313: May be harmful in contact with skin H317: May cause an allergic skin reaction H335: May cause respiratory irritation Precautionary Statements P260: Do not breathe dust/fume/gas/mist/vapours/spray.

www.abresist.com

P264: Wash hands thoroughly after handling

P270: Do not eat, drink or smoke when using this product.

P271: Use only outdoors or in a well-ventilated area

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection.

Response Statements

P337+P313If eye irritation persists:Get medical advice/attention.

P370+P378-In case of fire:Use appropriate mediafor extinction

P302+P353: IF ON SKIN: Wash with plenty of soap and waterfor extinction

P391: Collect spillage

P403+P235: Store in well ventilated place. Keep cool.

P501: Dispose of content and/or container in accordance with local, regional, national, and/or international regulations.

Hazard Description

This

HMIS-ratings (scale 0 - 4)		_
CHEMICAL NAME		
HEALTH	3	
FLAMMABILITY	1	
PHYSICAL HAZARD	0	
PERSONAL PROTECTION	F	

2.3 Other Hazards

None Known

This Material Safety Data Sheet is prepared to comply with the United States Occupational Safety and Health Administration (OSHA) Hazard Communication Standard (29 CFR 1910.1200). Unlisted ingredients are not "hazardous" per the OSHA standard.

Section 3: Hazards Identifications				
Chemical Name	CAS #	OSHA PEL*	ACGIH TLV*	WT%
Chemical Name	CAS #	OSHA PEL*	ACGIH TLV*	WT%
Poly(oxypropylendei)a mine	9046-10 -0	N/E	N/E	15-40
Nonyl phenol	84852-15-3	N/E	N/E	15-40
Benzyl alcohol	100-51-6	N/E	N/E	15-40
Cyclohexanedimethainna	2579-20-6	N/E	N/E	15-40
Polyamine	NJ TSRN# 5172130	00-6020P	N/E	10
1,3-dimethylbenzene	26139-75-3	N/E	N/E	5

*ALL INGREDIENTS ARE REGISTERED ON TSCA.

*Unless otherwise noted, all PEL and TLV Values are reported as 8 hour time weighted averages (TWA) *T/S - Trade Secret

Emergency Overview:		Mild or moderate eye irritation. May cause skin irritation. Harmful if swallowed.
HMIS RATING:		HEALTH-3, FLAMMABILITY-1, REACTIVITY-0 See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.
Potential Health Effec	ts	
	Eye contact:	Mild or moderate irritation, possible minor temporary cornea injury.

Chronic effects of ove	r exposure: NONE
Inhalation:	May cause nasal irritation, central nervous system depression or lung injury.
Skin absorption:	Not considered toxic.
Skin contact:	May cause skin irritation on prolonged or repeated exposure.
Eye contact:	Mild or moderate irritation, possible minor temporary cornea injury.

EMERGENCY & FIRST AID PROCEDURES:

Eyes:	Flush with plenty of water and get medical attention. Keep eye lids apart. Wash within 1 minute of contact for maximum results.
Skin:	Promptly wipe clean with paper or cloths and wash with soap and water. Remove contaminated clothing before reuse. Attention should be paid to hair, nose and eyes.
Inhalation: Ingestion:	In case of exposure to high concentration of vapor or mist, remove person to fresh air. If large amounts are swallowed, induce vomiting. Seek medical attention. May cause burns to mouth and throat.
Primary routes o	f entry: Inhalation, Ingestion, skin and eye contact.
Carcinogenity:	This product does not contain 0.1% or more of any substance which is listed as a carcinogen by NTP, IARC or OSHA.

Section 5: Fire Fighting Measures			
Flash Point:	234 F		
Test Method:	Setaflash Closed Cup		
Lower Flammability Limit:	N/A		
Upper Flammable Limit:	N/A		
Recommended Extinguishing Media:	Water, Foam, Carbon Dioxide, Dry Chemicals or Fog.		
Special Fire Fighting Procedures:	Firefighters should wear protective goggles and self contained breathing apparatus to avoid		
	inhalation of smoke or vapors. Remove all ignition sources.		
Unusual Fire or Explosion Hazards			
(conditions to avoid):			
	May produce hazardous fumes or hazardous decomposition products, such as carbon dioxide,		
	carbon monoxide, hydrogen sulfide, oxides of sulfur and nitrogen.		
	Section 6: Accidental Release Measures		
Special Protection:	Exposure to the spilled material may be irritating or harmful. Follow personal protective		
	equipment recommendations found in Section 8 of this MSDS. Additional precautions may be		
	necessary based on special circumstances created by the spill including; the material spilled,		
	the quantity of the spill, the area in which the spill occurred.		
Steps to be taken in case of material	s released or spilled:		
	Ventilate the area. Absorb spill with suitable absorbent material and place into a closed		
	container. Prevent material from entering waterways. Wear protective equipment during		
	cleanup. Use eye and skin protection.		
Transport Emergency Phone Number	: (INFOTRAC) 1-800-535-5053		
Section 7: Handling and Storage			
Handling:	Harmful or irritation material. Avoid contact and avoid breathing the material		
	Use only in a well ventilated area.		
Storogo			
Storage:	Store in a cool, dry place.		

Respiratory Protection:	If vapor or mist is generated and the occupational exposure limit is exceeded, use appropriate NIOSH/MSHA approved self-contained breathing equipment or a full face respirator. Respirators should be selected by and used following requirements found in OSHA's respirator standards (29 CFR 1910134). Not required for properly ventilation area.
Ventilation:	Local exhaust and general ventilation is recommended.
Hand Protection:	Nitrile Rubbers gloves.
Eye Protection:	Wear safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exits for eye contact with splashing or spraying liquid, or airborne material; Have an eye wash station available.
Skin and Body Protection:	Avoid skin contact by wearing chemically resistant gloves and long sleeved shirt. An apron may be appropriate if splashing can occur.
	Section 9: Physical and Chemical Properties
Physical state: Color: Odor: Weight by gallon: Solids (% by weight) V.O.C. Boiling range: Melting point: Density: Percent volatile: Vapor density (air=1): Vapor pressure (mm Hg):	Gel Gray Amine Odor 14 lbs 100 0 g/L 335 F N/E 1.04 N/D Not Volatile N/E
Evaporation rate: Water miscibility:	N/A <0.1%
	Section 10: Stability and Reactivity
Stability: Incompatibility: Hazardous polymerization: Hazardous decomposition products: Conditions to avoid:	Stable Strong oxiders, epoxy resin, and amine mixtures especially when hot. Will not occur. Oxides of Carbon and Phenolics under burning conditions Heat and warm storage
	Section 11: Toxicological Information
Chemical Name	LD50/LC50
Modified Aliphatic Polyamine	Not established
Overview:	Section 12: Ecological Information No ecological information available.

www.abresist.com

To the best of our knowledge, this product does not meet the definition of hazardous waste under U.S. EPA Hazardous Waste Regulations 40 CFR 261. Disposal via incineration at an approved facility is recommended. Consult state, local or provincial authorities for more restrictive requirements.

Section 14: Transport Information

Consult Bill of Lading for transportation information

DOT: CORROSIVE LIQUID N.O.S. IATA: CORROSIVE LIQUID N.O.S. Section 15: Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es): N/ASARA Hazard Classification:SARA Title III Regulations (40 CFR 370): N/ASARA Section 313 Listed Ingredients:This material does not contain any substance which is subject to the reporting
requirements of 40 CFR 372.DOT Proper Shipping Name:Amines, Liquid, Corrosive N.O.S. (Cycloaliphatic amine/nonylphenol)UN Number:UN1760

Section 16: Other Information

This information is furnished without warranty, representation inducement or license of any kind, except that is accurate to the best of KALENBORN knowledge, or obtained from sources believed by KALENBORN to be accurate and KALENBORN lnc. does not assure any legal responsibility for use reliance upon the same. Customers are encouraged to conduct their own tests. Before using any product, please read its label.

Revision Date: 06/2015