SAFETY DATA SHEET

Section 1 - CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name: #307-CERAMIC TILE ADHESIVE PART A

Company: POLYGEM INC.

PO Box 609

West Chicago, Illinois 60185

Telephone: 630-231-5600

630-231-5604 (Fax Line)

Emergency Telephone Number: 1-800-535-5053 USA

01-352-323-3444 International

Section 2 - HAZARDS IDENTIFICATION

GHS CLASSIFICATION OF SUBSTANCE OR MIXTURE:

Skin irritation: Category 2, H315 Skin Sensitization Category 1 H317 Eye irritation: Category 2, H319

GHS LABEL ELEMENTS:

HAZARD SYMBOLS:



SIGNAL WORD: Warning

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective

HAZARD STATEMENTS: H315 Causes skin irritation.

H315 Causes skin irritation

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS:

RESPONSE: P261 Avoid breathing mist/vapors/spray

P264 Wash hands thoroughly after handling.

P273 Avoid release to the environment.

P280 Wear protective gloves, clothing, and eye/face protection.

P302 + P352 IF ON SKIN: wash with plenty of soap and water

RESPONSE: P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. P333+P313 If skin irritation or rash occurs: Get medical attention.

P337+P313 If eye irritation persists: Get medical attention.

P362+P364 Take off contaminated clothing and wash it before reuse.

P391 Collect spillage.

STORAGE: Not applicable.

DISPOSAL: P501 Dispose of contents and containers in accordance with local, regional and

international regulations.

Precautionary statements are listed according to the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS) – Annex III

HMIS RATING:

CHEMICAL NAME		
HEALTH	2	
FLAMMABILITY	1	
PHYSICAL HAZARD	0	
PERSONAL PROTECTION	F	

See SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION for personal protective equipment recommendations.

Potential Health Effects

Eye contact: Mild or moderate irritation, possible minor temporary cornea injury. Skin contact: May cause skin irritation on prolonged or repeated exposure.

Skin absorption: Not considered toxic.

Inhalation: May cause nasal irritation, central nervous system depression or lung injury.

Chronic effects of over exposure: None

OSHA GHS Classification

This product is classified as hazardous as defined within the GHS OSH Hazard Communication Standard 29CFR1910 1200

Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Substances N/A

Concentration **Mixtures**

Bisphenol A Epoxy Resin 25058-	-99-8 N/E	N/E	>50
Calcium Carbonate 1317-6	65-3 N/E	N/E	>50
Silica, amorphous, fumed, crystalline free 112945	5-52-5 N/E	N/E	2
GHS/CLP: Skin irrt. 2 - H315; Skin Sens. 1 - H3	3117; Eye Irrt. 2 - H319		

^{*}ALL INGREDIENTS ARE REGISTERED ON TSCA.

Section 4 - FIRST AID MEASURES

Description of First Aid Measures

General advice: consult a physician; show this SDS to doctor in attendance.

In the event of skin contact: Drench the affected area immediately with plenty of water:

Remove contaminated clothing. Wash thoroughly with soap and water for at least 15 minutes

Seek medical attention if irritation, rash of other adverse effects occur.

In the event of eye contact: Bathe the eye with running water for at least 15 minutes, lifting the upper and

lower eye lids. Get medical attention if symptoms persist.

In the event of exposure by inhalation: Move person to fresh air. Get medical attention if symptoms develop

Most important symptoms and effects both acute and delayed

Skin irritation, allergic reactions.

Indication of immediate medical attention and special treatment needed

No specific antidote; treat symptomatically

Eye wash stations and emergency showers should be available.

Section 5 - FIRE FIGHTING MEASURES

Recommended Extinguishing Media: Foam, carbon dioxide, dry chemicals or fog. Use water spray to cool

fire exposed containers. Do not use direct water stream which may spread fire.

Special Fire Fighting Procedures: Firefighters should wear protective goggles and self contained breathing apparatus

to avoid inhalation of smoke or vapors. Remove all ignition sources.

^{*}Unless otherwise noted, all PEL and TLV Values are reported as 8 hour time weighted averages (TWA)

Unusual Fire or Explosion Hazards

Exposure to decomposition products may be harmful to health; combustion products may include but are not limited to: carbon monoxide, carbon dioxide, phenolics, aldehydes; smoke may contain particles of the original material as well. Prevent fire-fighting waters from entering sewer or waterways.

Advice for fire fighters: Use protective fire fighting clothing and positive pressure selfcontained breathing apparatus to protect against potential harmful and/or irritating fumes. Do not use high volume water jet as this may spread the area of the fire.

additional eye protection such as chemical splash goggles and/or face shield when the possibility exits for eye contact with splashing or spraying liquid, or airborne material; Have an eye wash station available.

Skin and Body Protection: Avoid skin contact by wearing chemically resistant gloves and long sleeved

shirt. An apron may be appropriate if splashing can occur.

Section 9: Physical and Chemical Properties

Physical state: Gel
Color: White

Odor: Aromatic Odor

 Weight by gallon:
 15 lbs.

 Solids (% by weight)
 100

 V.O.C.
 0 g/L

Boiling range:280 FMelting point:N/ADensity:1.2

Percent volatile: 0 by Weight Vapor density (air=1): Heavier than air

Vapor pressure (mm Hg): N/A
Evaporation rate: N/A
Water miscibility: Limited

Section 10: Stability and Reactivity

Stability: Stable

Incompatibility: Strong Oxidizers, acids, bases and epoxy hardeners under controlled conditions.

Hazardous polymerization: Will not occur.

Hazardous decomposition products: Carbon Monoxide, Carbon Dioxide, smoke. Others Unknown.

Conditions to avoid: Heat and warm storage.

Section 11: Toxicological Information

<u>Chemical Name</u> <u>LD50/LC50</u>

Epoxy Resin Not established

Section 12: Ecological Information

Overview: No ecological information available.

Page 3 of 4 <u>www.polygem.com</u>

Section 13: Disposal Considerations

provincial authorities for more restrictive requirements.

Section 14: Transport Information

Consult Bill of Lading for transportation information

DOT: Not Regulated **IATA**: Not Regulated

Section 15: Regulatory Information

OSHA Hazard Communication Standard (29 CFR 1910.1200) Hazard Class(es): N/A

SARA Hazard Classification: SARA Title III Regulations (40 CFR 370): Acute

SARA Section 313 Listed Ingredients: This material does not contain any substance which is subject to the reporting

requirements of 40 CFR 372.

DOT Proper Shipping Name: n/a

UN Number: n/a

Section 16: Other Information

This information is furnished without warranty, representation inducement or license of any kind, except that is accurate to the best of Polygem Inc. knowledge, or obtained from sources believed by Polygem Inc. to be accurate and Polygem Inc. does not assure any legal responsibility for use reliance upon the same. Customers are encouraged to conduct their own tests. Before using any product, please read its label.

Revision Date: 01/2015

Page 4 of 4 <u>www.polygem.com</u>