

# 307 FR-LITE

Order online or call  
www.brickintheyard.com  
Ph: (214)575-5600

## FIRE RETARDANT LIGHT-WEIGHT SCULPTURING EPOXY

- 25% LIGHTER FORMULA
- NO SOLVENTS
- NON-TOXIC
- SANDABLE
- PAINTABLE
- PIGMENTABLE

BUY DIRECTLY FROM  
BITY MOLD SUPPLY

- \* ENVIRONMENTALLY SAFE
- \* **CLEANS UP WITH WATER**
- \* **CLASS 1 FIRE RATING**

307 FR -LITE is a 100% solids class 1 Fire Rated, light-weight epoxy system specially formulated to a trowelable paste consistency for sculpturing and fabricating projects. 307 FR -LITE will cure into an extremely strong and light-weight plastic that is easily sanded or shaped. 307 FR -LITE can be tinted or painted and will even accept stains. 307 FR -LITE bonds well to most surfaces including fiberglass, foams, metal, wood and concrete. 307 FR -LITE is solvent free so it won't melt or dissolve foam surfaces.

307 FR -LITE can be used as a sculpturing or texturing veneer over other surfaces and is thick enough for immediate embossing upon placement. 307 FR -LITE is ideal for indoor or outdoor exhibit projects where strength and durability are desired. 307 FR -LITE can also be used as a patching compound to repair broken or damaged exhibits.

### PROPERTIES OF 307-FR LITE

Compressive Strength ASTM D-695	11,500 psi (min)
Tensile Strength ASTM D-638	2,100 psi (min)
Viscosity	Thick paste
Mix Ratio	1:1
Pot Life	60 minutes @70° F
Cure Time	10-14 hours
Weight per Gallon	8.25 lbs.
Packaging	2, 10, and 100 Gallon Kits

### MIXING INSTRUCTIONS

Thoroughly mix equal amounts of Part A and Part B by volume until streak free. Wearing protective gloves, trowel or spread the 307 FR - LITE and immediately texture, emboss or finish as desired. Small amounts of water may be used to help prevent the 307 FR - LITE from sticking to the gloves.

BITY Mold Supply  
521 Sterling Dr  
Richardson, TX 75081

www.brickintheyard.com  
Ph: (214)575-5600  
info@brickintheyard.com