

CAMMO FLEX

FLEXIBLE SCULPTURING EPOXY

- NO SOLVENTS
- NON-TOXIC
- PAINTABLE
- PIGMENTABLE
- UV RESISTANT

* ENVIRONMENTALLY SAFE

CAMMO FLEX is a 100% solids epoxy system specially formulated to provide a flexible surface for sculpturing and modeling projects. CAMMO FLEX will cure into a durable rubber that will accommodate movement and even bend upon cure.

CAMMO FLEX is available in a non tinted liquid or gel formulas and can be pigmented or painted. CAMMO FLEX is ideal for vines, trees, and leaves or other projects that require a more "lifelike" texture or feel. CAMMO FLEX is furnished in convenient pre-measured kits for easy and accurate mixing of the product.

PROPERTIES OF CAMMO FLEX

Compressive / Elongation	50+%
Tensile Strength ASTM D-638	1,000 p.s.i.
Viscosity	Pourable or Gel
Mix Ratio	2:1 by Volume
Pot Life	60 minutes @70• F
Cure Time	12 hours initial cure
Packaging	3 or 15 Gallon Kits

Mixing and Application Instructions

Add entire contents of the Part B container into the Part A container. Using a mixing stick or slow speed drill, thoroughly mix until streak free while being careful to avoid whipping air into the mixture. Apply the CAMMO FLEX by hand, brush or trowel to surface in thin layers up to 1/4" thick. Allow a 6 hour initial cure before applying additional layers of CAMMO FLEX and allow 24 hour cure before coating or painting the CAMMO FLEX.

BITY Mold Supply
521 Sterling Dr
Richardson, TX 75081

www.brickintheyard.com
Ph: (214)575-5600
info@brickintheyard.com