

Order online or call
www.brickintheyard.com
Ph: (214)575-5600

E-Z CAST

CASTING EPOXY

- NO SOLVENTS
- NON-TOXIC
- PAINTABLE
- PIGMENTABLE

* ENVIRONMENTALLY SAFE

E-Z CAST is a 100% solids casting epoxy system. E-Z CAST will cure into an extremely durable plastic. E-Z CAST can be tinted or painted. E-Z CAST bonds well to most surfaces including fiberglass, metal, wood and concrete. E-Z CAST is solvent and isocyanate free.

E-Z CAST is ideal for small or intricate detail castings where strength and durability are desired.

PROPERTIES OF E-Z CAST

Compressive Strength ASTM D-695	14,500 psi (min)
Tensile Strength ASTM D-638	5,500 psi (min)
Viscosity	Heavy oil
Mix Ratio by weight	14:1
Mix Ratio by Volume	8:1
Pot Life	40 minutes @70°F
Cure Time	8-12 hours
Packaging	Pint, Quart, Gal. & 2 Gal. Kits

MIXING INSTRUCTIONS

Mix 14 Parts A and 1 Part B by weight or 8 Parts A with 1 Part B by volume. Wearing protective gloves, mix the two parts together until streak free and uniform in color. Employ a vacuum chamber to achieve a bubble free casting.

BITY Mold Supply
521 Sterling Dr
Richardson, TX 75081

www.brickintheyard.com
Ph: (214)575-5600
info@brickintheyard.com