



Brick in the Yard
Mold Supply
brickintheyard.com
(214)575-5600
521 Sterling Dr
Richardson, TX 75081

Rigid Casting Foam Part B¹⁻⁶

Safety Data Sheet

According to Federal Register/Vol. 77, No.58/Monday, March 26, 2012/Rules and Regulations
Revision Date: 9/08/2015 Date of issue: 09t/08/2015

SECTION 1: IDENTIFICATION

1.1. Product Identifier

Product Form: Mixture

Product Name: Rigid Casting Foam B Component (polymeric MDI)

1.2. Intended Use of the Product

Use of the substance/mixture: Component of a two-part polyurethane system.

1.3. Name, Address, and Telephone of the Responsible Party

Company
Brick in the Yard
521 Sterling Dr
Richardson, TX 75081
(214) 575-5600

1.4 Emergency Telephone Number

Emergency Number : Chemtrec (800) 424-9300 or (703)527-3887

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2: H315

Eye Dam. 1: H318

2.2. Label Elements

Hazard Pictograms (GHS-US)



Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H315 - Causes skin irritation.

H318 - Causes serious eye damage.

: P264 - Wash hands, forearms, and exposed areas thoroughly after handling.

P280 - Wear eye protection, face protection, face protection, protective clothing, protective gloves.

P302±P352 - IF ON SKIN: Wash with plenty of soap and water.

P305±P351±P338 - If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing

P310 - Immediately call a POISON CENTER or doctor/physician

P321 - Specific treatment (see Section 4)

P332±P313 - If skin irritation occurs: Get medical advice/attention

P362 - Take off contaminated clothing and wash before reuse.

2.3. Other Hazards

Other Hazards Not Contributing to the Classification: Exposure may aggravate those with pre-existing eye, skin, or respiratory condition.

2.4. Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: HAZARDS IDENTIFICATION

3.1. Substance

Not applicable

3.2. Mixture

Name	Product Identifier	%	Classification (GHS-US)
Glycerol poly(oxyethylene) poly(oxypropylene) ether	(CAS No) 9082-00-2	50 - 80	Not classified
Water	(CAS No.) 7732-18-5	10 - 40	Not classified

Name	Product Identifier	%	Classification (GHS-US)
2-(Dimethylamino)ethanol	(CAS No) 108-01-0	<5	Flame. Liq. 3, H226 Acute Tox. 4 (oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 3 (Inhalation:vapour), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 STOT SE 3, H335 Aquatic Acute 3, H402

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label if possible).

First-aid Measures After Inhalation: Remove to fresh air and keep at rest in a position comfortable for breathing. Obtain medical attention if breathing difficulty persists.

First-aid Measures After Skin Contact: Rinse immediately with plenty of water. Obtain medical attention if irritation develops or persists.

First-aid Measures After Eye Contact: Rinse cautiously with water for at least 60 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.

First-aid Measures After Ingestion: Do NOT induce vomiting. Rinse mouth. Immediately call a POISON CENTER or doctor/physician.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/Injuries: Causes serious eye damage. Causes skin irritation.

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Eye Contact: Causes skin irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If you feel unwell, seek medical advice (show the label where possible).

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a Heavy water stream. Use of heavy stream of water may spread fire. Application of water stream to hot product may cause frothing and increase fire intensity.

5.2. Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reaction will not occur under normal conditions.

5.3. Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire.

Firefighting Instructions: Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.

Other Information: Refer to Section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray).

6.1.1. For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

6.1.2. For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Stop leak if safe to do so. Eliminate ignition sources. Ventilate area.

6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and Material for Containment and Cleaning Up

For Containment: Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Prepare a decontamination solution of 0.2%-0.5% liquid detergent and 3-8% concentrated ammonium hydroxide in water (5-10% sodium carbonate may be substituted for ammonium hydroxide). Allow deactivated material to stand for at least 30 minutes before shoveling into drums. Do not tighten the bungs. Mixing with wet earth is also effective, but slower. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials.

Incompatible Products: Strong acids. Strong bases. Strong oxidizers.

7.3. Specific End Use(s)

Component of a two-part polyurethane system.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

No Occupational Exposure Limits (OELs) have been established for this product or its chemical components.

8.2. Exposure Controls

Appropriate Engineering Controls

: Ensure adequate ventilation, especially in confined areas. Emergency fountains and safety showers, should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Protective goggles. Gloves. Protective clothing. Face shield.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear chemically resistant protective gloves.

Eye Protection

: Chemical goggles or safety glasses. Face shield.

Skin and Body Protection

: Wear suitable protective clothing

Respiratory Protection

: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupation Exposure Limits.

Environmental Exposure Controls

: Do not allow the product to be released into the environment.

Consumer Exposure Controls

: Do not eat, drink or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State

: Liquid

Odor

: Amine like, or organic odor

Odor Threshold

: No data available

pH

: No data available

Relative Evaporation Rate (butylacetate=1)

: No data available

Melting Point

: No data available

Freezing Point

: No data available

Boiling Point

: No data available

Flash Point

: >110°C(>230°F)

Auto-ignition Temperature

: No data available

Decomposition Temperature

: No data available

Flammability (solid, gas)

: No data available

Vapor Pressure

: No data available

Relative Vapor Density at 20°C

: No data available

Relative Density

: No data available

Specific Gravity

: No data available

Solubility

: No data available

Partition coefficient: n-octanol/water

: No data available

Viscosity

: No data available

9.2. Other Information No additional information available.

SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Hazardous reactions will not occur under normal conditions.
10.2. Chemical Stability: Stable under recommended handling and storage conditions (see section 7).
10.3. Possibility of Hazardous Reactions: Hazardous polymerization will not occur.
10.4. Conditions to Avoid: Direct sunlight. Extremely high or low temperatures. Ignition sources. Incompatible materials.
10.5. Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.
10.6. Hazardous Decomposition Products: Carbon oxides (CO, CO₂). Nitrogen oxides. Hydrogen cyanide.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

Glycerol poly(oxyethylene) poly(oxypropylene) ether (9082-00-2)	
LD50 Oral Rat	>10 g/kg
2-(Dimethylamino)ethanol (108-01-0)	
LD50 Oral Rat	1803 mg/kg
LD50 Dermal Rabbit	1220 mg/kg
LC50 Inhalation Rat (ppm)	1641 ppm/4h

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye damage.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Carcinogenicity: Not classified.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity(Single Exposure): Not classified

Specific Target Organ Toxicity (Repeated Exposure): Not classified

Aspiration Hazard: Not classified.

Symptoms/Injuries After Inhalation: May cause respiratory irritation.

Symptoms/Injuries After Skin Contact: Causes skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye damage.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: None expected under normal conditions of use.

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

2-(Dimethylamino)ethanol (108-01-0)	
LC50 Fish 1	81 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	98.77 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 Other Aquatic Organisms 1	35 mg/l (Exposure time: 72 h - Species: Desmodesmus subspicatus)

12.2. Persistence and Degradability No additional information available.

12.3. Bioaccumulative Potential

2-(Dimethylamino)ethanol (108-01-0)	-0.55 (at 23°C)
Log Pow	

12.4. Mobility in Soil No additional information available

12.5. Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste treatment methods

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

14.1. In Accordance with DOT Not regulated for transport.

14.2. In Accordance with IMDG Not regulated for transport.

14.3. In Accordance with IATA Not regulated for transport.

SECTION 15: REGULATORY INFORMATION

15.1 US Federal Regulations

UTC - Water Blown B Component (Polyurethane resin blend with Amine Catalyst)	
SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Glycerol poly(oxyethylene) poly(oxypropylene ether (9082-00-2)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

2-(Dimethylamino)ethanol (108-01-0)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

Water (7732-18-5)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	

15.2 US State Regulations

Glycerol poly(oxyethylene) poly(oxypropylene) ether (9082-00-2)	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

2-(Dimethylamino)ethanol (108-01-0)	
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 1	
U.S. - Massachusetts - Oil & Hazardous Material List - Groundwater Reportable Concentration - Reporting Category 2	
U.S. - Massachusetts - Oil & Hazardous Material List - Reportable Quantity	
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 1	
U.S. - Massachusetts - Oil & Hazardous Material List - Soil Reportable Concentration - Reporting Category 2	
RTK - U.S. - Massachusetts - Right To Know List	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - 24-hour	
U.S. - New Hampshire - Regulated Toxic Air Pollutants - Ambient Air Levels (AALs) - Annual	
RTK - New Jersey - Right to Know Hazardous Substance List	
U.S. - Texas - Effects Screening Levels - Long Term	
U.S. - Texas - Effects Screening Levels - Short Term	

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision date	: 11/09/2015
Other information	: This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 3 (Inhalation: vapour)	Acute toxicity (inhalation:vapour) Category 3
Acute Tox. 4 (Dermal)	Acute Toxicity (dermal) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1B	Skin corrosion/irritation Category 1B
Skin Irrit. 2	Skin corrosion/irritation Category 2
STOT SE 3	Specific target organ toxicity (single exposure) Category 3
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H318	Causes serious eye damage
H331	Toxic if inhaled
H335	May cause respiratory irritation
H402	Harmful to aquatic life

NFPA Health Hazard	: 2 - Intense or continued exposure could cause temporary incapacitation or possible residual injury unless prompt medical attention is given.
NFPA Fire Hazard	: 1 - Must be preheated before ignition can occur.
NFPA Reactivity	: 1 - Normally stable, but can become unstable at elevated temperatures and pressures or may react with water with some release of energy, but not violently.



HMIS III Rating : 2 Moderate Hazard
: 1 Slight Hazard
Health
Flammability : 1 Slight Hazard
Physical

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

