# SAFETY DATA SHEET



**Date Prepared:** 05/20/2008

SDS No: TC-800 PART B

**Date Revised:** 06/13/2017

**Revision No: 2** 

# TC-800 PART B

# 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** TC-800 PART B **GENERAL USE:** Polyurethane curative

#### **MANUFACTURER**

BJB Enterprises, Inc. 14791 Franklin Avenue Tustin, CA 92780

**Emergency Phone:** (714) 734-8450

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (USA & Canada): (800) 424-9300

or (703) 527-3887 CCN# 2820

## 2. HAZARDS IDENTIFICATION

#### **GHS CLASSIFICATIONS**

#### Health:

Eye Irritation, Category 2A Carcinogenicity, Category 2

## Physical:

Flammable Liquids, Category 4

# **GHS LABEL**



Health hazard



Exclamation mark

SIGNAL WORD: WARNING

# HAZARD STATEMENTS

H227: Combustible liquid.

H319: Causes serious eye irritation. H351: Suspected of causing cancer.

# PRECAUTIONARY STATEMENTS

# **Prevention:**

P201: Obtain special instructions before use.

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P264: Wash thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

## Response:

P370+P378: In case of fire: Use water spray, carbon dioxide, dry chemical, or foam for extinction.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P308+P313: IF exposed or concerned: Get medical advice/ attention.

## Storage:

P403: Store in a well-ventilated place.

P405: Store locked up.

Disposal:

P501: Dispose of contents/container in accordance with local/regional/national/international regulations.

#### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Hydroxy terminated poly(oxyalkylated) polyol	15 - 40	102-60-3
Polyether polyol mixture	10 - 30	Proprietary
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	10 - 30	68515-49-1
Solvent naphtha (petroleum), heavy aromatic	5 - 10	64742-94-5
Naphthalene	< 0.1	91-20-3

#### 4. FIRST AID MEASURES

**EYES:** Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if irritation or rash develops. Wash clothing before reuse.

**INGESTION:** If swallowed, call a physician immediately. Do not induce vomiting unless directed to do so by medical personnel. Provided the patient is conscious, wash out mouth with water. Never give anything by mouth to an unconscious person.

INHALATION: Remove to fresh air. Seek medical attention if breathing becomes difficult or if respiratory irritation develops.

**NOTES TO PHYSICIAN:** Symptomatic and supportive therapy as needed. Following severe exposure medical follow-up should be monitored for at least 48 hours.

#### 5. FIRE FIGHTING MEASURES

**GENERAL HAZARD:** Combustible

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical, or foam.

HAZARDOUS COMBUSTION PRODUCTS: Carbon monoxide and carbon dioxide.

**FIRE FIGHTING PROCEDURES:** Cool fire exposed containers with water spray. Remove containers from the fire area if possible. Do not release runoff from fire control methods to sewers or waterways.

**FIRE FIGHTING EQUIPMENT:** Firefighters should wear positive pressure self-contained breathing apparatus (SCBA) and consider use of unmanned hose holders or monitor nozzles for fighting large fires.

SENSITIVE TO STATIC DISCHARGE: This material can accumulate static charges which can cause an incendiary electrical discharge.

# 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL: Eliminate sources of ignition.** Evacuate the area. Clean-up should only be performed by trained personnel. People dealing with a major spill should wear full protective clothing including appropriate respiratory protection. Prevent product spill from entering sewers or waterways. Neutralize small spills with a decontaminant.

**LARGE SPILL:** Contain and absorb large spills onto an inert, non-flammable adsorbent carrier (such as earth or sand). Do not use combustible materials such as saw dust. Use only spark resistant and explosion proof recovery devices. Shovel into open-top drums or plastic bags for further decontamination, if necessary. Wash the spill area clean with a liquid decontaminant. Remove and properly dispose of residues. Notify applicable government authorities if release is reportable. (See CERCLA in Section 15).

#### ENVIRONMENTAL PRECAUTIONS

WATER SPILL: Do not discharge into drains or rivers.

GENERAL PROCEDURES: Refer to section 8 of SDS for personal protection details.

**RELEASE NOTES:** Composition and extent of any spill should be evaluated against local regulations and reported to the proper agencies, if necessary.

# 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Keep away from sources of ignition. Avoid contact with eyes, skin and clothing. Use only with adequate ventilation. Avoid breathing vapor over open containers. Avoid open container exposure to damp air. Avoid breathing aerosols, mists, and vapors.

**HANDLING:** Use appropriate personal protective equipment as specified in Section 8. Handle in a well-ventilated area. Handle and use in a manner consistent with good industrial/manufacturing techniques and practices.

**STORAGE:** Store in a dry and well-ventilated place, away from excessive heat in the original or similar container. Avoid sources of ignition and incompatible materials. Protect from freezing. Containers should be tightly sealed to prevent contamination with foreign materials. Avoid unnecessary contact.

**STORAGE TEMPERATURE:** 65-80°F (18-27°C)

SHELF LIFE: 6 months from date of shipment under manufacturers recommended storage conditions.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

## **EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29				
	EXPOSU	JRE LIN	MITS	·
Chemical Name	Туре	Туре		mg/m <sup>3</sup>
Hydroxy terminated poly(oxyalkylated) polyol	OCHA DEL	TWA	-	-
	OSHA PEL	STEL	-	-
	ACGIH TLV	TWA	ı	-
		STEL	ı	-
	NIOSH REL -	TWA	ı	-
	NIOSH KEL	STEL	ı	-
	OSHA PEL	TWA	-	-
		STEL	-	-
Polyether polyol mixture	ACGIH TLV	TWA	-	-
Polyeiner polyoi mixture	ACOM ILV	STEL	-	-
	NIOSH REL -	TWA	-	-
	NIOSH KEE	STEL	-	-
	OSHA PEL	TWA	-	-
	OSINTEL	STEL	-	-
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	ACGIH TLV	TWA	-	-
1,2 201201100100100100101000		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
	OSHA PEL	TWA	-	-
		STEL	-	-
Solvent naphtha (petroleum), heavy aromatic	ACGIH TLV	TWA	-	-
1 4 //		STEL	-	-
	NIOSH REL	TWA	-	-
		STEL	-	-
Naphthalene  ACGIH TLV  NIOSH REL	OSHA PEL	TWA	10	50
		STEL	-	-
	ACGIH TLV	TWA	10	52
		STEL	15	79
	NIOSH REL	TWA	10	50
		STEL	15	75

**ENGINEERING CONTROLS:** Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits.

# PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Safety goggles or glasses are recommended. Plastic face shields should be used for complete face protection to protect against possible splashing or spraying of material. ANSI Z87.1 or approved equivalent.

**SKIN:** Chemical-resistant gloves and chemical goggles, face-shield, and synthetic apron or coveralls should be used to prevent contact with eyes, skin, or clothing. Wear nitrile or neoprene gloves. Chemical resistant gloves lined with polyethylene offer maximum protection.

**RESPIRATORY:** Exhaust ventilation recommended. An organic vapor cartridge or fresh air supplied respirator (NIOSH approved) may be necessary for certain applications. Consider the type of application, environmental concentrations, and other materials being used concurrently when determining respirator use and selection. Observe OSHA regulations for respirator use (29 CFR 1910.134).

**PROTECTIVE CLOTHING:** Protective clothing should be selected and used in accordance with 'Guidelines for the Selection of Chemical Protective Clothing' published by ACGIH.

**WORK HYGIENIC PRACTICES:** Contaminated clothing should be changed and washed before reuse. Eating, drinking and smoking in immediate work area should be prohibited. Wash hands before eating.

**OTHER USE PRECAUTIONS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Training is important. Follow all label precautions.

#### 9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Aromatic
COLOR: Colorless
pH: No data available

PERCENT VOLATILE: 6.71

FLASH POINT AND METHOD: 76.7°C (170°F) Pensky-Martens CC

VAPOR PRESSURE: No data available VAPOR DENSITY: No data available BOILING POINT: No data available

**SOLUBILITY IN WATER:** Partially soluble

**SPECIFIC GRAVITY:** 1.01 (water=1) at 25°C (77°F)

**VISCOSITY #1:** 375 Centipoise at 25°C (77°F)

(VOC): < 6.78 g/l Calculated. Theoretical VOC minus water and exempt solvents.

#### 10. STABILITY AND REACTIVITY

**REACTIVITY:** Hazardous reactions will not occur under normal transport or storage conditions. **STABILITY:** This product is stable under normal ambient conditions of temperature and pressure.

**CONDITIONS TO AVOID:** High temperatures and sources of ignition.

POSSIBILITY OF HAZARDOUS REACTIONS: None Known

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide and carbon dioxide.

**INCOMPATIBLE MATERIALS:** Isocyanates, strong bases, strong acids, and strong oxidizing agents.

# 11. TOXICOLOGICAL INFORMATION

# **ACUTE TOXICITY**

Chemical Name	ORAL LD <sub>50</sub>	DERMAL LD <sub>50</sub>	INHALATION LC <sub>50</sub>
Hydroxy terminated poly(oxyalkylated) polyol	3280 mg/kg Rat	> 2000 mg/kg Rabbit	No data available
Polyether polyol mixture	No data available	No data available	No data available
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	> 10 g/kg Rat	> 3.16 g/kg Rabbit	> 0.13 mg/l Rat
Solvent naphtha (petroleum), heavy aromatic	> 5000 mg/kg Rat	> 2000 mg/kg Rabbit	No data available
Naphthalene	490 mg/kg Rat	20000 mg/kg Rabbit	> 0.4 mg/l Rat (4 h)

SKIN CORROSION/IRRITATION: No data available

**SERIOUS EYE DAMAGE/IRRITATION:** Causes serious eye irritation.

RESPIRATORY OR SKIN SENSITISATION: No data available

GERM CELL MUTAGENICITY: No data available

#### CARCINOGENICITY

Chemical Name	NTP Status	IARC Status
Naphthalene	2	2B

REPRODUCTIVE TOXICITY: No data available STOT-SINGLE EXPOSURE: No data available STOT-REPEATED EXPOSURE: No data available ASPIRATION HAZARD: No data available

#### 12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: No data available

**ECOTOXICOLOGICAL INFORMATION:** No specific ecological data are available for this product. Refer to Section 6 for information regarding accidental release and Section 15 for regulatory reporting information.

BIOACCUMULATION/ACCUMULATION: No data available

DISTRIBUTION: No data available

CHEMICAL FATE INFORMATION: No data available

#### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protections and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

#### 14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION): Not Regulated

AIR (ICAO/IATA): Not Regulated VESSEL (IMO/IMDG): Not Regulated

## 15. REGULATORY INFORMATION

#### UNITED STATES

# SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Acute Health Hazard, Chronic Health Hazard, Fire Hazard

**313 REPORTABLE INGREDIENTS:** This product does not contain any substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

# CERCLA (COMPREHENSIVE ENVIRONMENTAL RESPONSE, COMPENSATION, AND LIABILITY ACT)

**CERCLA REGULATORY:** For this/these chemicals, release of more than the Reportable Quantity to the environment in a 24-hour period requires notification to the National Response Center (800-424-8802 or 202-426-2675):

Chemical Name	Wt.%	CERCLA RQ
Naphthalene	< 0.1	100 lbs.

#### TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA REGULATORY: This product does not contain any chemicals subject to TSCA Section 12(b) export notification.

**TSCA STATUS:** This product or its components are listed in or exempt from the TSCA inventory requirements.

# OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR1910.119---PROCESS SAFETY MANAGEMENT OF HIGHLY HAZARDOUS CHEMICALS: None of the chemicals in this product are considered highly hazardous by OSHA.

**CALIFORNIA PROPOSITION 65:** This product contains chemical(s) which are known to the State of California to cause cancer, birth defects or other reproductive harm, and may be subject to the requirements of California Proposition 65 (CA Health & Safety Code Section 25249.5):

Chemical Name	Wt.%	Listed
1,2-Benzenedicarboxylic acid, di-C9-11-branched alkyl esters, C10-rich	10 - 30	Developmental Toxicity
Naphthalene	< 0.1	Cancer

OSHA HAZARD COMM. RULE: The contents of the SDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200. CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): This product has been classified according to the hazard criteria of the CPR and the SDS contains all the information required by the CPR.

**DOMESTIC SUBSTANCE LIST (INVENTORY):** All components in this product are listed in or exempted from the Domestic Substances List (DSL) or the Non-Domestic Substances List (NDSL).

#### **GENERAL COMMENTS:**

**DIDP RESTRICTIONS:** This product contains diisodecyl phthalate (DIDP), CAS# 68515-49-1 EINECS# 271-091-4. In the U.S., there is an interim prohibition on DIDP above 0.1 percent by weight (one thousand parts per million) in toys intended for children age 12 and under that can be placed in a child's mouth and child care articles for children age 3 and under [H.R. 4040, The Consumer Safety Improvement Act of 2008]. In the EU, DIDP shall not be used as substance or as constituents of preparations, at concentrations of greater than 0.1 percent by weight (one thousand parts per million) of the plasticized material, in toys and child care articles which can be place in the mouth by children. Such toys and child care articles containing DIDP in concentrations greater than the limit mentioned above shall not be placed on the market [Directive 2005/84/EC].

## 16. OTHER INFORMATION

**REASON FOR ISSUE:** Revision

Date Revised: 06/13/2017

**REVISION SUMMARY:** This SDS replaces the 08/05/2013 SDS.

HMIS RATING

HEALTH *	1
FLAMMABILITY	2
PHYSICAL HAZARD	0
PERSONAL PROTECTION	X



HMIS RATINGS NOTES: Personal Protection: See Section 8

MANUFACTURER DISCLAIMER: This information is furnished without warranty, expressed or implied, except that is accurate to the best knowledge of BJB Enterprises, Inc. The data on this sheet relates only to the specific material designated herein. BJB Enterprises, Inc. assumes no legal responsibility for use or reliance upon this data.