SCULPT NOUVEAU

Safety Data Sheet



Health2Fire2Reactivity1Personal
ProtectionH

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Name:	VINYL RESIN SPRAY
Chemical Name:	Vinyl Resin
Trade Name:	Vinyl Resin Spray
Product Use:	Paint for various surfaces
Distributor's Name:	Sculpt Nouveau
Distributor's Address:	1155 Industrial Ave. Escondido, CA 92029
Emergency Phone:	CHEMTREC 800-424-9300 U.S. and Canada; +1-703-527-3887 International
Business Phone:	899-432-8242

2. HAZARDS IDENTIFICATION

Hazard Identification:	This product is classified as a hazardous substance as assessed in accordance with OSHA 29 CFR 1910.1200. DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. FLAMMABLE LIQUID AND VAPOR. MAY CAUSE AN ALLERGIC SKIN REACTION. <u>Hazard Statements</u> (H): H317 - May cause allergic skin reaction. H226 Flammable liquid and vapor. <u>Precautionary Statements</u> (P): P210 - Keep/Store away from heat/sparks/open flames/hot surfaces - No Smoking. P240 - Ground/bond container and receiving equipment. P233 - Keep container tightly closed. P243 - Take precautionary measures against static charge. P280 - Wear protective gloves/eye protection. P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301 - Do NOT induce vomiting. P261 - Avoid breathing mist/sprays. P272 - Contaminated work clothing should not be allowed out of the workplace. P302+P352 - IF ON SKIN: Wash with plenty of soap and water. P333+P313 - If skin irritation or rash occurs: Get medical medical /attention. P321 - Specific treatment - see section 4 of this SDS. P370+P378 - In case of fire: Use carbon dioxide, foam or dry chemical fire extinguisher. P363 - Wash contaminated clothing before reuse. P403+P235 - Store in a cool, well ventilated place, keep cool. P501 - Dispose of contents/container to licensed treatment storage facility.			
Effects of Exposure:	Eyes: Irritation upon direct contact. Skin: Irritation and possible dermatitis. Ingestion: Irritation to gastrointestinal tract Inhalation: Inhalation of high vapor concentrations may cause CNS effects, headache, dizziness.			
Symptoms of Overexposure:	Eyes:Redness, burning, irritation, and swelling around eyes.Skin:Redness, burning, itching, rash, and scaling of the skin (dermatitis).Ingestion:Nausea and vomiting.Inhalation:Coughing, irritation in mucous membranes, difficulty breathing.			
Acute Health Effects:	May be fatal if swallowed and enters airways. May cause an allergic skin reaction. May be harmful if swallowed. Breathing of high vapor concentrations may cause headaches, stupor, irritation of throat and eyes.			
Chronic Health Effects:	May damage the nervous system, kidney and/or liver.			
Target Organs:	Eyes, skin, lungs.			

3. COMPOSITION & INGREDIENT INFORMATION

CHEMICAL NAME(S)	CAS No.	%	EXP	OSURE L	IMITS IN	AIR (mg/	′m ₃) ppr	n		
			AC	GIH	OS	HA		NOF	ISC	
			TLV	STEL	TWA	STEL	IDLH	TWA	STEL	
Non-Hazardous Trade Secret	N/A	1-10	NA	NA	NA	NA	NA	NF	NF	
Xylene	1330-20-7	10-30	NE	NE	NE	NE	NA	NA	NF	
Resin-Vinyl	N/A	20-30	NA	NA	NA	NA	NA	NA	NF	
Acetone	67-64-1	10-30	217	NA	217	NA	NA	NF	NF	
Methyl Ethyl Ketone	78-93-3	10-30	NA	NA	NA	NA	NA	NF	NF	

NA = Not Available; ND = Not Determined; NE = Not Established; NF = Not Found;

All WHMIS required information is included. It is located in appropriate sections based on the ANSI Z200.1-2010 format.

Safety Data Sheet

4. FIRST AID MEASURES

First Aid:	Ingestion:	DO NOT INDUCE VOMITING. Contact nearest Poison Control Center for assistance and instructions. Seek immediate medical attention. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
	Eyes:	If product gets in eyes, flush eyes thoroughly with large amounts of water for at least 15 minutes, holding eyelid(s) open to ensure complete flushing. If the eyes or face become swollen during or following use, consult a physician or emergency room immediately.
	Skin:	Remove contaminated clothing and wash affected areas with soap and water. If discomfort or a skin reaction occurs, contact a physician. Do not wear contaminated clothing until cleaned.
	Inhalation:	Remove victim to fresh air at once. Seek immediate medical attention if breathing is diffucult.
	To Physycian:	Administration of adsorbents such as activated charcoal may be of value. Gastric lavage may be effective when performed by a physician within 4 hours of ingestion.
Medical Conditions Aggravated by Exposure:		matitis, other skin conditions, and disorders of the eyes or respiratory system or impaired kidney more susceptible to the effects of this substance.

5. FIREFIGHTING MEASURES

Fire and Explosion Hazard :	Does not sustain combustion but will burn under fire conditions. Over-heated drums may rupture. Heavy vapors can travel to source of ignition and flash back.
Extinguishing Methods :	Use carbon dioxide, foam, dry chemical.
Firefighting Procedures :	As with any fire, firefighters should wear appropriate protective equipment including a NIOSH approved or equivalent self contained breathing apparatus and protective clothing. Fight fires as for surrounding materials. Water may be used to cool containers. If water is used, fog nozzles are preferred.

6. ACCIDENTAL RELEASE MEASURES

Spills:	Before cleaning any spill or leak, individuals involved in spill cleanup must wear appropriate personal protective equipment (PPE). Use safety glasses and face shield, gloves and other protective clothing to prevent skin contact. Insure adequate ventilation. Eliminate all source of sparks (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind. Absorb spillage with inert material and dispose of in accordance of E.P.A. and other local, state and federal authorities. For waste disposal methods, consult federal, state and local regulations. Place in closed containers. Dispose of product in accordance with these regulations.

7. HANDLING & STORAGE INFORMATION

Work and Hygiene Practices:	Avoid breathing mists or spray. Avoid eye and skin contact. Wear protective equipment when handling product. Keep out of the reach of children. Do not eat, drink or smoke when handling this product. Wash thoroughly after handling. Do not expose to heat and flame, keep away from sparks. Use only in ventilated areas. Immedi- ately clean up and decontaminate any spills or residues.
Storage and Handling:	Use and store in a cool, dry, well ventilated location (e.g., local exhaust ventilation, fans), away from heat and sources of ignition, keep away from sparks. Ground and bond all transfer equipment.
Special Precautions:	Empty containers may retain hazardous product residues. Do not reuse empty containers for other purposes.

8. EXPOSURE CONTROLS & PERSONAL PROTECTION

Ventilation and Engineering Controls:	Use local or general exhaust ventilation to effectively remove and prevent buildup of vapors or mist generated from the handling of this product. Ensure appropriate equipment is available (eye wash station, sink, etc.).
Respiratory Protection:	NIOSH/OSHA approved respirator types suitable for materials in section 2 recommended. Approved chemical or mechanical filters recommended when ventilation is restricted. Do not breathe vapors or spray mist. Wear appropriate respirator during and after application unless air monitoring records vapor/mist levels below acceptable limits. Follow manufacturer directions for use.
Eye Protection:	Safety glasses with side shields must be used when handling this product. A face shield is also recommended.
Hand Protection:	Wear protective, chemical-resistant gloves, (e.g., neoprene) when handling this product.
Body Protection:	A chemical resistant apron and protective clothing are recommended when handling or using this product.

9. PHYSICAL & CHEMICAL PROPERTIES

Appearance:	Colored liquid
Odor:	Solvent odor
Odor Threshhold:	N/A
pH:	N/A
Melting and Freezing Point:	N/A
Boiling Point/Range:	145°C (293.0°F) Initial
Flashpoint:	31°C (87.8°F) Setaflash closed cup
Flammability Limits:	N/A
Vapor Pressure:	3.3 kPa
Vapor Density:	4.3
Relative Density:	N/A
Solubility:	Insoluble
Evaporation Rate:	N/A
VOC	(g/l): 150

10. STABILITY & REACTIVITY

Stability:	table at normal temperatures and pressures.	
Hazardous Decomposition:	Dxides of carbon and nitrogen	
Hazardous Polymerization:	Vill not occur	
Conditions to Avoid:	Excessive heat, freezing, changes in temperature	
Incompatible Substances:	Strong oxidizing agents, acids and strong bases.	

11. TOXICOLOGICAL INFORMATION

Routes of Entry:	Inhalation: Yes	Absorption: Yes	Ingestion: Yes			
Toxicity Data:	Xylene: LD50 (oral, rat) = 3608 g/kg: LD50 (dermal, rabbit) = 14100 mg/kg. Acetone: LD50 (oral, rat) = 5800 mg/kg:					
	LD50 (dermal, rabbit) = 1410	LD50 (dermal, rabbit) = 14100 mg/kg. MEK: LD50 (oral, rat) = 2000 mg/kg: LD50 (dermal, rabbit) = 2000 mg/kg				
Acute Toxicity:	See section Section 2 for a	See section Section 2 for acute toxicity				
Chronic Toxicity:	See section Section 2 for cl	hronic toxicity				
Suspected Carcinogen:	This product does not cont	tain chemicals known to the	State of California to cause re	productive harm.		
Reproductive Toxicity:	This product is not reported to cause mutagenic effects in humans or animals.					
Mutagenicity:	This product is not reported to cause mutagenic effects in humans or animals.					
Embryotoxicity:	This product is not reporte	d to cause embryotoxic effec	ts in humans.			
Teratogenicity:	This product does not cota	in any chemicals that have te	eratogenic effects in humans.	,		
Irritancy of Product:	See Section 2					
Biological Exposure Indices:	NE					
Physician Recommendations:	Treat symptomatically					

Safety Data Sheet

12. ECOLOGICAL INFORMATION

Environmental Stability	No data available
Effects on Plants & Animals:	No data available
Effects on Aquatic Life:	<u>Xylene</u> : LC50: 16.1 mg/L/96h (Lepomis macrochirus) LC50: 13 mg/L/24h (Carassius auratus) <u>Acetone</u> : LC50: 5540 mg/L/96h (Rainbow Trout) <u>MEK</u> : LC50: 100 mg/L/96h (Pimephales Promelas)

13. DISPOSAL CONSIDERATIONS

Waste Disposal:	Review current local, state and federal laws, codes, statutes and regulations to determine current status and appropriate disposal method for the ingredients listed in Section 2. Any disposal practice must be in compliance with local, state, and federal laws and regulations. Contact the appropriate agency for specific information. Treatment, transport, storage and disposal of hazardous waste must be provided by a licensed facility or waste hauler.
Special Considerations:	N/A

14. TRANSPORTATION INFORMATION

49 CFR (GND)		
IATA (AIR)		
IMDG (OCN)		
TDGR (Canadian GND)		
ADR/RID (EU)		
SCT (MEXICO)		
ADGR (AUS)		

UN1263 Paint 3, III

15. REGULATORY INFORMATION

SARA Reporting Requirements:	This product does not contain substances subject to SARA Title III, section 313 reporting requirements.
SARA Threshold Planning Quantity	N/A
TSCA Inventory Status:	The components of this product are listed on the TSCA Inventory.
Federal and State Regulations:	WARNING: This product contains chemicals known to the State of California to cause cancer and birth defets or other reproductive harm. Acetone is found on the following state criteria lists: Right-to-Know List, CA, NJ, PA MN and MA Xylene is found on the following state criteria lists: Right-to-Know List, NJ, PA, RI, IL and MA
Other Canadian Regulations:	This product has been classified according to the hazard criteria of the CPR and the SDS contains all of the information required by the CPR. The components of this product are listed on the DSL/NDSL. None of the components of this product are listed on the Priorities Substances List. WHMIS Class B2(Flammable Liquid).
CERCLA Reportable Quantity:	N/A
Other Federal Requirements:	NAA
Other Requirments:	The primary components of this product are listed in Annex 1 of EU Directive 67/548/EEC. Flammable. Irritating to eyes, respiratory tract and skin. Keep out of reach of children. Keep container tightly closed. Keep container in a well ventilated place. Keep way from sources of ignition. No smoking. Do not breathe fumes/mists/vapor spray.

Safety Data Sheet

16. OTHER INFORMATION

Other Information:	DANGER! MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAY. Flammable liquid and vapor. May cause an allergic skin reaction. Keep away from heat/sparks/open flames/hot surfaces. No Smoking.
Disclaimer:	This Safety Data Sheet is offered pursuant to OSHA's Hazard Communication Standard, 29 CFR §1910.1200. Other government regulations must be reviewed for applicability to this product. To the best of Sculpt Nouveau's knowledge, the information contained herein is reliable and accurate as of this date; however, accuracy, suitability or completeness are not guaranteed and no warranties of any type, either expressed or implied, are provided. The information contained herein relates only to the specific product(s). If this product(s) is combined with other materials, all component properties must be considered. Data may be changed from time to time. Be sure to consult the latest edition.
Prepared For:	Sculpt Nouveau 1155 Industrial Ave. Escondido, CA 92029 USA Tel: 760 432 8242 www.sculptnouveau.com