


Features

- · Low profile door design
- Ideal for remodeling with a 1" (25 mm) flange
- \bullet Clean interior due to hidden shelf adjustments that move at 1/2" (13 mm) increments
- Mirrored interior
- Includes installation hardware for recess mounting
- Can be recessed or surface mounted (surface mounting kit required)
- Slow-close functionality
- Can be installed with left or right opening

Construction

- Satin anodized aluminum body
- 3 mirror design rear of cabinet and both sides of door
- Grass 108° self-closing hinges with 3 way adjustability
- Safeseal® Gasket with sealed corners on cabinet body



Dimensions

Height: 26-1/8" (664 mm) Width: 24" (610 mm)

Depth: 5-1/16" (129 mm) When surface mounted

1-1/16" (27 mm) When recessed

Options

- Polished edge or beveled front mirror
- Other widths and heights available

Installation Options

 $\label{eq:continuous_problem} \begin{tabular}{ll} \textbf{Recessed Mount} - Rough Opening - 24" H x 22" W x 4" D \\ \textbf{(610 mm H x 559 mm W x 102 mm D)} \\ \textbf{Surface Mount} - Reference Surface Mount Kit when ordering RSMK26D4P - Polished Edge Mirror Side Kit \\ \end{tabular}$

Model Number Key						
Series	Cabinet	Width	Height	Depth	Mirror Edge	Number of Doors
R	С	24"	26"	D4	FP = Flat, Polished	1
					FB = Flat Beveled	

