

SAFETY DATA SHEET T-CUT ORIGINAL

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1. Product identifier

Product name T-CUT ORIGINAL
Product No. NCR500, SFD102, TCO002, TCO005, TCT304, TCT375, TCT501, TCT504, TCT506

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Car maintenance product.

1.3. Details of the supplier of the safety data sheet

Manufacturer TETROSYL LIMITED
BEVIS GREEN WORKS
WALMERSLEY
BURY
BL9 6RE
0161 764 5981
0161 797 5899
info@tetrosyl.com

1.4. Emergency telephone number

0161 764 5981

SECTION 2: HAZARDS IDENTIFICATION

2.1. Classification of the substance or mixture

Classification (EC 1272/2008)

Physical and Chemical Hazards	Flam. Liq. 3 - H226
Human health	Skin Irrit. 2 - H315; Eye Irrit. 2 - H319; STOT SE 3 - H336
Environment	Aquatic Chronic 2 - H411

Classification (1999/45/EEC) Xi; R36/38. N; R51/53. R10, R67.

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.
Environment

The product contains a substance which is toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

2.2. Label elements

Detergent Labelling:

>= 30%	Aliphatic hydrocarbons
5 - < 15%	anionic surfactants
< 5%	non-ionic surfactants

Label In Accordance With (EC) No. 1272/2008



T-CUT ORIGINAL

Signal Word	Warning	
Hazard Statements	H226	Flammable liquid and vapour.
	H315	Causes skin irritation.
	H319	Causes serious eye irritation.
	H336	May cause drowsiness or dizziness.
	H411	Toxic to aquatic life with long lasting effects.
Precautionary Statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	P210	Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
	P271	Use only outdoors or in a well-ventilated area.
	P273	Avoid release to the environment.
	P280	Wear protective gloves/protective clothing/eye protection/face protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
	P337+313	If eye irritation persists: Get medical advice/attention.
	P405	Store locked up.
	P501	Dispose of contents/container in accordance with local regulations.
Supplementary Precautionary Statements	P233	Keep container tightly closed.
	P240	Ground/bond container and receiving equipment.
	P241	Use explosion-proof electrical equipment.
	P242	Use only non-sparking tools.
	P243	Take precautionary measures against static discharge.
	P261	Avoid breathing vapour/spray.
	P264	Wash contaminated skin thoroughly after handling.
	P321	Specific treatment (see medical advice on this label).
	P370+378	In case of fire: Use foam, carbon dioxide, dry powder or water fog for extinction.
	P303+361+353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P312	Call a POISON CENTER or doctor/physician if you feel unwell.
	P332+313	If skin irritation occurs: Get medical advice/attention.
	P362	Take off contaminated clothing and wash before reuse.
	P391	Collect spillage.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.
	P403+235	Store in a well-ventilated place. Keep cool.

2.3. Other hazards**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2. Mixtures**

T-CUT ORIGINAL

2-2'-(OCTADEC-9-ENYLIMINO)BISETHANOL		1-5%
CAS-No.: 25307-17-9	EC No.: 246-807-3	Registration Number: 01-2119510876-35-0000
Classification (EC 1272/2008) Acute Tox. 4 - H302 Skin Corr. 1A - H314 Aquatic Acute 1 - H400	Classification (67/548/EEC) Xn;R22. C;R35. N;R50.	
AMMONIA ...%		<0.5
CAS-No.: 1336-21-6	EC No.: 215-647-6	
Classification (EC 1272/2008) Skin Corr. 1B - H314 STOT SE 3 - H335 Aquatic Acute 1 - H400	Classification (67/548/EEC) C;R34 N;R50	
PETROLEUM DISTILLATES		10-30%
CAS-No.: 64742-82-1	EC No.: 265-185-4	
Classification (EC 1272/2008) Flam. Liq. 3 - H226 EUH066 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. N;R51/53. R10,R66,R67.	
PETROLEUM DISTILLATES		30-60%
CAS-No.: 64742-81-0	EC No.: 265-184-9	Registration Number: 01-2119462828-25-XXXX
Classification (EC 1272/2008) Skin Irrit. 2 - H315 STOT SE 3 - H336 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC) Xn;R65. Xi;R38. N;R51/53. R67.	

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: FIRST AID MEASURES

4.1. Description of first aid measures

General information

Get medical attention if any discomfort continues. Remove affected person from source of contamination.

General first aid, rest, warmth and fresh air.

Inhalation

In case of inhalation of spray mist: Move person into fresh air and keep at rest. Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

T-CUT ORIGINAL

Ingestion

Immediately rinse mouth and drink plenty of water. If person becomes uncomfortable or if ingested in large amounts (50-100 ml for an adult person): Take to hospital along with these instructions.

Skin contact

Promptly wash contaminated skin with soap or mild detergent and water. Promptly remove clothing if soaked through and wash as above.

Eye contact

Immediately flush with plenty of water for up to 15 minutes. Remove any contact lenses and open eyes wide apart. Do not rub eye. Get medical attention if any discomfort continues.

4.2. Most important symptoms and effects, both acute and delayed

General information

The severity of the symptoms described will vary dependant of the concentration and the length of exposure. NOTE! Effects may be delayed. Keep affected person under observation.

Inhalation

May cause an asthma-like shortness of breath. Vapours may cause drowsiness and dizziness.

Ingestion

May cause discomfort if swallowed. May cause stomach pain or vomiting. May cause nausea, headache, dizziness and intoxication.

Skin contact

Prolonged or repeated contact with skin may cause redness, itching, irritation and eczema/chapping.

Eye contact

May cause temporary eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

No recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY!

SECTION 5: FIREFIGHTING MEASURES

5.1. Extinguishing media

Extinguishing media

Use fire-extinguishing media appropriate for surrounding materials. Extinguish with foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

Unusual Fire & Explosion Hazards

No unusual fire or explosion hazards noted.

5.3. Advice for firefighters

Special Fire Fighting Procedures

No specific fire fighting procedure given.

Protective equipment for fire-fighters

Leave danger zone immediately.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

Avoid inhalation of vapours and aerosol spray. Provide adequate ventilation. In case of spills, beware of slippery floors and surfaces. For personal protection, see section 8.

T-CUT ORIGINAL**6.2. Environmental precautions**

Do not allow ANY environmental contamination. Do not discharge into drains, water courses or onto the ground. The product should not be dumped in nature but collected and delivered according to agreement with the local authorities.

6.3. Methods and material for containment and cleaning up

Stop leak if possible without risk. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate. Provide ventilation and confine spill. Do not allow runoff to sewer. Collect with absorbent, non-combustible material into suitable containers.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: HANDLING AND STORAGE**7.1. Precautions for safe handling**

Good personal hygiene is necessary. Wash hands and contaminated areas with water and soap before leaving the work site. Do not eat, drink or smoke when using the product. Avoid forming spray/aerosol mists. Provide good ventilation. Read and follow manufacturer's recommendations. Do not handle broken packages without protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep upright. Store in tightly closed original container.
Storage Class
Flammable liquid storage.

7.3. Specific end use(s)

The identified uses for this product are detailed in Section 1.2.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**8.1. Control parameters**

Name	STD	TWA - 8 Hrs		STEL - 15 Min		Notes
AMMONIA ...%	WEL		18 mg/m ³		25 mg/m ³	
PETROLEUM DISTILLATES	WEL		600 mg/m ³			
PETROLEUM DISTILLATES	WEL		800 mg/m ³			

WEL = Workplace Exposure Limit.

8.2. Exposure controls

Protective equipment



Engineering measures

Provide adequate ventilation. Observe Occupational Exposure Limits and minimise the risk of inhalation of vapours. Must not be handled in confined space without sufficient ventilation.

Respiratory equipment

If ventilation is insufficient, suitable respiratory protection must be provided.

T-CUT ORIGINAL**Hand protection**

For prolonged or repeated skin contact use suitable protective gloves. Nitrile gloves are recommended, but be aware that the liquid may penetrate the gloves. Frequent change is advisable.

Eye protection

Wear approved, tight fitting safety glasses where splashing is probable.

Other Protection

Wear appropriate clothing to prevent repeated or prolonged skin contact. Provide eyewash station.

Hygiene measures

Wash contaminated clothing before reuse. Wash promptly with soap & water if skin becomes contaminated.

Wash hands after contact. When using do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**9.1. Information on basic physical and chemical properties**

Appearance	Liquid
Colour	Beige.
Odour	Slight odour. Ammonia.
Solubility	Forms an emulsion with water.
Initial boiling point and boiling range (°C)	>100°C
Melting point (°C)	Scientifically unjustified.
Relative density	1.050 - 1.070 g/cm ³ 20°C
Vapour density (air=1)	Scientifically unjustified.
Vapour pressure	Scientifically unjustified.
Evaporation rate	Scientifically unjustified.
pH-Value, Conc. Solution	Scientifically unjustified.
Viscosity	2000 - 2600 cP 20°C
Decomposition temperature (°C)	Scientifically unjustified.
Odour Threshold, Lower	Scientifically unjustified.
Odour Threshold, Upper	Scientifically unjustified.
Flash point (°C)	41°C
Auto Ignition Temperature (°C)	Scientifically unjustified.
Flammability Limit - Lower(%)	Scientifically unjustified.
Flammability Limit - Upper(%)	Scientifically unjustified.
Partition Coefficient (N-Octanol/Water)	Scientifically unjustified.
Oxidising properties	Not determined.

9.2. Other information

None.

T-CUT ORIGINAL**SECTION 10: STABILITY AND REACTIVITY****10.1. Reactivity**

No specific reactivity hazards associated with this product.

10.2. Chemical stability

Stable under normal temperature conditions and recommended use.

10.3. Possibility of hazardous reactions

Not applicable.

10.4. Conditions to avoid

Avoid heat, flames and other sources of ignition.

10.5. Incompatible materials

Materials To Avoid

No specific, or groups of materials are likely to react to produce a hazardous situation.

10.6. Hazardous decomposition products

Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1. Information on toxicological effects**

Toxic Dose 1 - LD 50

>5000 (PETROLEUM DISTILLATES) mg/kg (oral rat)

Inhalation

Vapours may cause headache, fatigue, dizziness and nausea.

Ingestion

May cause discomfort if swallowed.

Skin contact

Product has a defatting effect on skin.

Eye contact

Visual disturbances including blurred vision

Health Warnings

INHALATION. May cause irritation to the respiratory system. SKIN CONTACT. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. EYE CONTACT. Irritating to eyes. INGESTION. May cause stomach pain or vomiting.

SECTION 12: ECOLOGICAL INFORMATION

Ecotoxicity

The product contains substances which are toxic to aquatic organisms and which may cause long term adverse effects in the aquatic environment.

12.1. Toxicity

LC 50, 96 Hrs, Fish mg/l	<30 mg/l (PETROLEUM DISTILLATES)
EC 50, 48 Hrs, Daphnia, mg/l	10 - 22 mg/l (PETROLEUM DISTILLATES)
IC 50, 72 Hrs, Algae, mg/l	4.6 - 10.0 mg/l (PETROLEUM DISTILLATES)

T-CUT ORIGINAL**12.2. Persistence and degradability**

Degradability

No data available.

12.3. Bioaccumulative potential

Bioaccumulative potential

No data available on bioaccumulation.

Partition coefficient

Scientifically unjustified.

12.4. Mobility in soil

Mobility:

The product is partly soluble in water. May spread in the aquatic environment.

Adsorption/Desorption Coefficient

Not available.

12.5. Results of PBT and vPvB assessment

Not Classified as PBT/vPvB by current EU criteria.

12.6. Other adverse effects

Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

General information

Waste is classified as hazardous waste. Disposal to licensed waste disposal site in accordance with the local Waste Disposal Authority.

13.1. Waste treatment methods

Confirm disposal procedures with environmental engineer and local regulations.

SECTION 14: TRANSPORT INFORMATION**14.1. UN number**

UN No. (ADR/RID/ADN) 1993

UN No. (IMDG) 1993

UN No. (ICAO) 1993

14.2. UN proper shipping name

Proper Shipping Name FLAMMABLE LIQUID, N.O.S. (PETROLEUM DISTILLATES, PETROLEUM DISTILLATES)

14.3. Transport hazard class(es)

ADR/RID/ADN Class 3

ADR/RID/ADN Class Class 3: Flammable liquids.

ADR Label No. 3

IMDG Class 3

ICAO Class/Division 3

Transport Labels

T-CUT ORIGINAL

**14.4. Packing group**

ADR/RID/ADN Packing group	III
IMDG Packing group	III
ICAO Packing group	III

14.5. Environmental hazards

Environmentally Hazardous Substance/Marine Pollutant
No.

14.6. Special precautions for user

EMS	F-E, S-E
Emergency Action Code	3Y
Hazard No. (ADR)	30

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code**SECTION 15: REGULATORY INFORMATION****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

EU Legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments.

15.2. Chemical Safety Assessment

No chemical safety assessment has been carried out.

SECTION 16: OTHER INFORMATION

Revision Comments

NOTE: Lines within the margin indicate significant changes from the previous revision.

Revision Date	19/09/2012
Revision	26
Supersedes date	02/09/2011 v25
Safety Data Sheet Status	Approved.

T-CUT ORIGINAL

Risk Phrases In Full

R34	Causes burns.
R35	Causes severe burns.
R10	Flammable
R22	Harmful if swallowed.
R65	Harmful: may cause lung damage if swallowed.
R36/38	Irritating to eyes and skin.
R37	Irritating to respiratory system.
R38	Irritating to skin.
R66	Repeated exposure may cause skin dryness or cracking.
R51/53	Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R67	Vapours may cause drowsiness and dizziness.
R50	Very toxic to aquatic organisms.

Hazard Statements In Full

EUH066	Repeated exposure may cause skin dryness or cracking.
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H335	May cause respiratory irritation.
H336	May cause drowsiness or dizziness.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.