



LS-400

Media Station



- All-in-One Device to Offer Up to 4 Full HD Video Sources Capturing, Mixing, Switching, Recording and Live Streaming
- Mobile Mini Controller and Touch-Friendly Graphical User Interface Makes Live Production Easier
- Fully Integrated with Kaltura, Panopto and Opencast Video Management Systems

Main Features

Capture Up to 4 Video Sources at the Same Time

Via HDMI, VGA, RJ-45 interfaces or streaming inputs, AREC LS-400 supports up to 4 Full HD 1080p video sources capturing, mixing, switching, recording and live streaming. Users can choose 1 mixed video plus 4 individual videos recording for flexible use. LS-400 can mix audio via HDMI, 3.5mm stereo audio jacks and AREC wireless microphone.



Intuitive and Versatile Control Options

AREC Online Director supports a wide range of control options, including Web Browser (IE, Firefox), Software Application (Windows, Mac OS), Touch-Friendly Graphical User Interface(GUI)*, and Mini Controller from Mobile Device. With Mini Controller, AREC LS-400 can be accessed via browsers on Android or iOS phones and tablets – no particular apps required. Control buttons on the front of LS-400 are also provided.


*The on-screen GUI supports mouse device control through USB connection.



On-screen GUI & USB Interface*



Web/ SW-based Online Director



Mini Controller from Mobile Device


Broadcast Your Mixed Video

LS-400 can stream mixed video to up to 2 platforms simultaneously, such as YouTube, Facebook, Twitch and other live broadcasting websites.




Real-Time Assistant in Video Making

With AREC Online Director, LS-400 allows users to be in control of their video recording/streaming in real-time. It makes users easily switch and mix between sources, add or remove backgrounds and overlay graphics (titles) for live production.



AREC Video Manager : Videos with Just One Click

With the built-in video management platform, administrators or teachers can manage videos stored in the local Media Station remotely. They can download, upload or delete a video file, and edit video information. With available APIs, all of the video content, metadata, and thumbnail can be accessed seamlessly for third party integration.



Backup & Upload Your Recordings

With internal 1TB hard drive, LS-400 can save hundreds of hours recording videos. To increase security, LS-400 can automatically backup or upload recordings to AREC Media-Center, FTP, SFTP, Opencast, Kaltura, Panopto and so on.



SATA 1TB HDD




OPENCAST Panopto KALTURA
FTP Backup




Product Interface

Front View



Back View



On-Screen Graphical User Interface



- 1 Overlay Images
- 2 Recording Layouts
- 3 Background
- 4 Custom Theme
- 5 Timer
- 6 Start / Stop Streaming
- 7 Start / Stop Recording
- 8 Snapshot
- 9 Playback Video
- 10 Setting
- 11 LS-400 IP Address
- 12 Audio Volume Bar
- 13 Display Switch

Specifications

Model Name	AREC LS-400
Input Connection	
Video Input Interface	HDMI: 2 channels/ VGA: 2 channels/ RJ-45: 4 channels (Supports AREC Full HD network camera)/ IP Streaming: 4 channels Note : Supports DVI and component video cable inputs with appropriate DVI to HDMI or component to VGA adapters
Max. Video-In channels	Maximum 4 channel synchronized recording HDMI/ VGA: up to 2 channels Full HD network camera: up to 4 channels
Resolution Range	HDMI: 480i~1080p60 VGA: 480i~1080p60 RTP/ RTMP/ RTSP, Max.: 1080p30
Audio-in Channels	3.5mm Stereo Mic in: 1 channel; 3.5mm Stereo Line in: 1 channel; Wireless Mic: 1 channel; HDMI: 2 channels
Video Processing	
Compression	H.264 / AVC
Frame Rate	Max. 30fps
Bit Rate	300Kbps~8Mbps
Resolution	Max. 1080p (640x360 ~ 1920x1080)
Audio Processing	
Compression	AAC-LC
Bit Rate	80Kbps~320Kbps
Video / Audio Outputs	
Video Outputs	1x HDMI display port 1x VGA display port (1 output option from loop-through, inputs monitoring and multi-source display) 2x H.264/AVC digital video over Ethernet Note: on-screen GUI is selectable between HDMI and VGA display port
Output Resolution	1080p60
Audio Outputs	3.5mm Stereo Line out: 1 channel; HDMI: 1 channel
Streaming	
Streaming Delay	1 sec.
Compatible Streaming Input Protocols	RTSP, RTP, RTMP
Streaming Output Protocols	RTP, RTMP (RTMPS), RTSP Note: 1. Users can choose 1 output option from RTP or RTMP only 2. RTP: MPEG2-TS over RTP unicast; MPEG2-TS over RTP multicast 3. RTSP (TCP/ UDP): Max 6 clients RTSP streams available via public URL (example: pulled streams)
Storage, Backup, and Compatibility	
Built-in Local Storage	1TB 2.5" SATAIII Hard Drive
External Storage	Supports USB drive recording through the front port
Locally Stored File Format	MP4
FTP Backup	Automatic backup to an FTP or SFTP server after recording is done
Third-Party Software Server	Compatible with Opencast, Panopto and Kaltura

Recording	
Recording Modes	Mixed mode, 1 Mixed + 4 individual original sources
Recording Layouts	34 layouts for user-defined, including full screen/ picture-in-picture/ picture-by-picture/ multi-channel split screen
Bookmark	Automatic and manual bookmark insertion
Background Images	Multiple for user-defined
On-Screen Images	Multiple for user-defined
Custom Theme	Multiple for user-defined, setting from web-based back stage
Live Broadcasting	
Live Broadcast to CDN or Stream Server	Yes, support RTMP (RTMPS) protocol. Stream up to 2 platforms simultaneously
Video Information Editing	
Post Video Info Editing	Yes, through Video Manager web page
Video Info Adding	Video info will be added on video file name automatically while file output or uploading
Controls of LS-400 and Network Camera	
Touch Interface	Through recommended touch screen interactive projector or interactive module
Mouse Device and Numeric Keypad	Through USB interface connection
Video Switcher	Yes, through AREC Online Director (web-based or desktop applications) or on-screen GUI for manual controls
Mini Controller	Through mobile web browser and wireless connection for manual controls
External Control	Yes, supports RS-232 interface port
Control Button	Yes, at the front of the media station
Video Manager Platform	Built-in video manager platform: through web-based control interface
Camera Control	VISCA/ PELCO-D/ PELCO-P/ ONVIF profile S
General Information	
Operation System	Embedded Linux system
Power Supply	12V / 2A
Temperature / Humidity	0~40°C / 90%
Dimension	366.4 mm(L) x 187.3mm(W) x 53.1mm(H)
Weight	2.27kg (5 lbs)
Language	SC/ TC/ English/ Russian/ Spanish/ Czech/ Korean/ Latvian
Accessories	Power adapter/ quick guide/ wireless Mic antenna/ wireless USB numeric keypad
Recommended AREC Products	
AREC Auto-Tracking System AREC Network Camera CI Series AREC Wireless Microphone	



AREC Inc. | www.arec.com | sales@arec.com

Exclusive Representative in Europe, Africa, Latin America and CIS Countries

ADENA Limited | www.a-dena.com

E-MAIL: yakov@a-dena.com

TEL: +886-2-8712-1882

AREC reserves the right to modify product specifications without prior notice.