


Gauge Adaptor SMA20



Direct Gauge Adaptor SMD20

Gauge Adaptor SMA20
Direct Gauge Adaptor SMD20



Thread	Dimensions (mm/in)		Order Codes NBR	FPM* (Standard Option-North America)
	h	Hex A		
G	54	19		
G1/4	2.13	.75	SMA20-G1/4-P-OR-C6F	SMA20-G1/4-V-OR-C6F
G1/2	64	27	SMA20-G1/2-P-OR-C6F	SMA20-G1/2-V-OR-C6F
	2.52	1.06		
1/4 NPT	54	19	SMA20-1/4NPT-P-C6F	SMA20-1/4NPT-V-C6F
	2.13	.75		
1/2 NPT	64	27	SMA20-1/2NPT-P-C6F	SMA20-1/2NPT-V-C6F
	2.52	1.06		
7/16-20 UNF	54	19	SMA20-7/16UNF-PC6F	SMA20-7/16UNF-V-C6F
	2.16	.75		
9/16-18 UNF	57	19	SMA20-9/16UNF-P-C6F	SMA20-9/16UNF-V-C6F
	2.24	.75		
G1/4	41	19	SMD20-G1/4-P-OR-C6F	SMD20-G1/4-V-OR-C6F
	1.61	.75		
G1/2	51	27	SMD20-G1/2-P-OR-C6F	SMD20-G1/2-V-OR-C6F
	2.01	1.06		
1/4 NPT	41	19		SMD20-1/4NPT-C6F
	1.61	.75		
1/2 NPT	51	27		SMD20-1/2NPT-C6F
	2.01	1.06		
7/16-20 UNF	41	19		SMD20-7/16UNF-C6F
	1.61	.75		
9/16-18 UNF	43	19		SMD20-9/16UNF-C6F
	1.69	.75		

Metal Parts

Standard material: Steel, zinc/nickel-plated = **C6F (Cr-VI-free)**
 For ordering V2A (1.4305 / AISI 303) replace "C6F" with "V2A".
 For ordering V4A (1.4571 / AISI 316Ti) replace "C6F" with "V4A".

Sealings

For ordering FPM sealings replace "P" with "V".
 For ordering EPDM sealings replace "P" with "E".

* **Standard option for North America is FPM (Viton®).**

Snubber on request.

Dimensional drawings: All dimensions in mm (in).