

# ATF SUPER

universal automatic gear oil; fulfils the requirements of DEXRON II D

## Description

ATF SUPER is a versatile transmission fluid manufactured on the basis of specifically selected base oils and corresponding additives. They give the product optimum lubricating properties, resulting in a good-quality and reliable application.

## Advantages

- broad application spectrum
- good shear stability
- highly resilient
- good switching properties
- especially also for older vehicles
- neutral seal behaviour

## Field of application

ATF SUPER can be used as a universal ATF for a wide range of applications where ATF DEXRON II with the corresponding specifications is required. For example, in automatic transmissions, steering gears, hydrostatic transmissions and power transmission systems.

## Notes

Please observe the manufacturer's instructions.

## Specifications

DEXRON® II D; TYP A / TASA; ALLISON C4; CATERPILLAR TO-2.; MERCON

## Safety + Performance

MAN 339 Typ V1; MAN 339 Typ Z1; MB 236.6; VOLVO 97335; VOITH H55.6335.xx; ZF TE-ML-04D; ZF TE-ML-05L; ZF TE-ML-09; ZF TE-ML-11A; ZF TE-ML-14A; ZF TE-ML-17C; ZF TE-ML-21L

## Technical data

Properties	Unit	Test according to	Values
Colour			red
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.865
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	38.9
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	7.6
Viscosity index		DIN ISO 2909	168
Pourpoint	°C	ASTM D5950	-45
Flash point C.O.C.	°C	DIN EN ISO 2592	>200
Brookfield	mPa·s	ASTM D 2983	-40 / 47000

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

