

Printing date 03/22/2016

Reviewed on 03/22/2016

1 Identification

- · Product identifier
- · Trade name: CROSS POWER 4T SAE 10W/50
- Application of the substance / the mixture Engine oil Only for proper handling.
- Details of the supplier of the safety data sheet
 Manufacturer/Supplier:

BUCHER_AG_LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse_31__ CH-4901_Langenthal__ Telefon_+41_(0)62_919_75_75

Lube-Tech Lubrication Technologies, Inc. 900 Mendelssohn Avenue North US-55427 Golden Valley, Minnesota Phone: 001 763 417 1357

· Information department: <u>msds@motorex.com</u>

• *Emergency telephone number:* Toxicological Information Centre CH-8028 Zurich <u>info@toxi.ch</u> T. +41 (0)44 251 51 51 USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

Safety Data Sheet acc. to OSHA HCS

2 Hazard(s) identification

· Classification of the substance or mixture

GHS07

Skin Sens. 1 H317 May cause an allergic skin reaction.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

- · GHS label elements
- The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



· Signal word Warning

- Hazard-determining components of labeling: Ca long-chain alkaryl sulfonate
- · Hazard statements
- H317 May cause an allergic skin reaction.


(Contd. on page 2)

⁻ ÚS

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: CROSS POWER 4T SAE 10W/50



· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

112-41-4	dodec-1-ene	60-80%
	Flam. Liq. 4, H227	
	Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts	1-2.5%
	♦ Eye Dam. 1, H318; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; Aquatic Acute 2, H401	
	Alkyl phenol	0.25-1%
	♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Skin Irrit. 2, H315	
	Ca long-chain alkaryl sulfonate	0.25-1%
	() Skin Sens. 1, H317	

4 First-aid measures

· Description of first aid measures

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

(Contd. on page 3)

Printing date 03/22/2016

Reviewed on 03/22/2016

(Contd. of page 2)

Trade name: CROSS POWER 4T SAE 10W/50

- After skin contact: Remove residues with soap and water. Remove contaminated clothing immediately. Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Consult a physician if irritation develops.
 After swallowing:
- Do not induce vomitting. Do not take in resorption stimulating agents.
- Consult a physician who will decide on need and method of emptying the stomach.
- Information for doctor:
- *Most important symptoms and effects, both acute and delayed* No further relevant information available.
- Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- \cdot Special hazards arising from the substance or mixture
- In case of fire carbon, sulphur and nitrogen oxides can be formed. • Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Not required. • Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system.
- Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
 Absorb with liquid-binding material (sand_diatomite_acid_binders_up)
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.
 See Section 13 for disposal information.

7 Handling and storage

· Handling:

· Precautions for safe handling

Used oils (motor oils, gear oils, industrial oils) contain components causing skin cancer. Therefore, avoid skin contact by wearing protecting gloves. Carefully clean soiled parts of the skin with soap.

Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

(Contd. on page 4)

us –

Safety Data Sheet

acc. to OSHA HCS

Reviewed on 03/22/2016

(Contd. of page 3)

Trade name: CROSS POWER 4T SAE 10W/50

- Information about protection against explosions and fires: Do not heat above flash point.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Store containers closed and protect against rain, dust, heat and other atmospheric influences.
- · Storage class: 10
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Additional information about design of technical systems: No further data; see item 7.

- · Control parameters
- **Components with limit values that require monitoring at the workplace:** The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- · Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection: Goggles recommended during refilling.

(Contd. on page 5)

LIS

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: CROSS POWER 4T SAE 10W/50

(Contd. of page 4)

Fluid Yellow - Brown Characteristic Not determined. Not determined. Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Yellow - Brown Characteristic Not determined. Not determined. Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Yellow - Brown Characteristic Not determined. Not determined. Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Not determined. Not determined. Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Not determined. Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Undetermined. Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Undetermined. > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
 > 200 °C (> 392 °F) Not applicable. 255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Not applicable.255 °C (491 °F) (DIN 51794)Not determined.Product is not selfigniting.
255 °C (491 °F) (DIN 51794) Not determined. Product is not selfigniting.
Not determined. Product is not selfigniting.
Product is not selfigniting.
U
Braduat daga not propert on avalagian bazard
Product does not present an explosion hazard.
Not determined.
Not determined.
Not determined.
0.86 g/cm³ (7.177 lbs/gal) (ASTM D 4052)
Not determined.
Not determined.
Not determined.
Not miscible or difficult to mix.
Not determined.
Not determined.
116 mm²/s @ 40 °C (DIN 51562-1)
0.0 g/l / 0.00 lb/gl No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.

- · Chemical stability
- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.

(Contd. on page 6) -US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: CROSS POWER 4T SAE 10W/50

(Contd. of page 5) • Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- on the skin: No irritant effect.
- on the eye: No irritating effect.
- · Sensitization: Sensitization possible through skin contact.
- Additional toxicological information: The product shows the following dangers according to internally approved calculation methods for preparations: Irritant

· Carcinogenic categories

· IARC (International Agency for Research on Cancer)

None of the ingredients is listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Harmful to aquatic organisms

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- **Recommendation:** Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 7)

US

Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

Trade name: CROSS POWER 4T SAE 10W/50

(Contd. of page 6)

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number DOT, ADR,ADN, ADN, IMDG, IATA	Void	
UN proper shipping name DOT, ADR,ADN, ADN, IMDG, IATA	Void	
Transport hazard class(es)		
DOT, ADR,ADN, ADN, IMDG, IATA Class	Void	
Packing group DOT, ADR,ADN, IMDG, IATA	Void	
Environmental hazards: Marine pollutant:	No	
Special precautions for user	Not applicable.	
<i>Transport in bulk according to Annex</i> <i>MARPOL73/78 and the IBC Code</i>	Il of Not applicable.	
UN "Model Regulation":	Void	

15 Regulatory information

- · Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

- · Section 313 (Specific toxic chemical listings):
- None of the ingredients is listed.
- · TSCA (Toxic Substances Control Act):

112-41-4 dodec-1-ene

26401-35-4 DTDA

Mineral oil

Phosphorodithioic acid, 0,0-di-C1-14-alkyl esters, zinc salts

8042-47-5 Mineralöl

Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

(Contd. on page 8)

Safety Data Sheet acc. to OSHA HCS

Printing date 03/22/2016

Reviewed on 03/22/2016

(Contd. of page 7)

us

Trade name: CROSS POWER 4T SAE 10W/50

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· National chemical directories

Components listed or exempted from listing: TSCA (USA) ENCS/METI (J) AICS (Aus) IECSC (CN) ECL/KECI (KOR) HSNO (NZ) PICCS (RP) DSL/NDSL (CDN) EINECS/ELINCS/NLP (EU)

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Abteilung Produktsicherheit

Date of preparation / last revision 03/22/2016 / -

Abbreviations and acronyms:
 Flam. Liq. 4: Flammable liquids, Hazard Category 4
 Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
 Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1
 Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
 Aquatic Acute 1: Hazardous to the aquatic environment - AcuteHazard, Category 2
 Aquatic Acute 2: Hazardous to the aquatic environment - AcuteHazard, Category 3
 Aquatic Chronic 1: Hazardous to the aquatic environment - Chronic Hazard, Category 1
 Aquatic Chronic 2: Hazardous to the aquatic environment - Chronic Hazard, Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 2
 Aquatic Chronic 3: Hazardous to the aquatic environment - Chronic Hazard, Category 2