115



Printing date 04/12/2016

Safety Data Sheet acc. to OSHA HCS

Reviewed on 04/12/2016

# 1 Identification

#### · Product identifier

# · Trade name: PROTEX SPRAY

- Application of the substance / the mixture
  Only for proper handling.
  Impregnation
- Details of the supplier of the safety data sheet
  Manufacturer/Supplier:

BUCHER\_AG\_LANGENTHAL MOTOREX-Schmiertechnik Bern-Zürich-Strasse\_31\_\_ CH-4901\_Langenthal\_\_ Telefon\_+41\_(0)62\_919\_75\_75

Lube-Tech Lubrication Technologies, Inc. 900 Mendelssohn Avenue North US-55427 Golden Valley, Minnesota Phone: 001 763 417 1357

· Information department: <u>msds@motorex.com</u>

• Emergency telephone number: Toxicological Information Centre CH-8028 Zurich <u>info@toxi.ch</u> T. +41 (0)44 251 51 51 USA + Kanada: 1 800 424 9300 (Chemtrec Chemical Manufacturers Association, Arlington, VA 22209)

### 2 Hazard(s) identification

· Classification of the substance or mixture					
GHS02	Flame				
Flam. Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurized container: May burst if heated.			
GHS09	Environment				
$\checkmark$					
Aquatic Chronic 2	2 H411	Toxic to aquatic life with long lasting effects.			
<b>GHS07</b>					
Skin Irrit. 2	H315	Causes skin irritation.			
Eye Irrit. 2A	H319	Causes serious eye irritation.			
STOT SE 3	H336	May cause drowsiness or dizziness.			
Aquatic Acute 2	H401	Toxic to aquatic life. (Contd. on page 2)			

Printing date 04/12/2016

Reviewed on 04/12/2016

#### Trade name: PROTEX SPRAY

	(Contd. of page 1
Label elem	
GHS label	
The product Hazard pic	t is classified and labeled according to the Globally Harmonized System (GHS).
<u> </u>	
<b>く砂&gt;く</b>	
GHS02 G	HS07 GHS09
Signal wor	<b>d</b> Danger
Hazard-det	ermining components of labeling:
	ns C6-C7, n-alkanes, iso-alkanes, cyclenes, <5% n-hexane
propan-2-ol	
, isopropyl ac	etate
Hazard sta	
	Extremely flammable aerosol. Pressurized container: May burst if heated.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.
H401	Toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
	ary statements
Precaution P210	
P210 P251	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
	Do not pierce or burn, even after use.
P211	Do not spray on an open flame or other ignition source.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P273	Avoid release to the environment.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P305+P351	+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable fo
	breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P332+P313	If skin irritation occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P302+P352	
P391	Collect spillage.
P362+P364	
P405	Store locked up.
P410+P412	
P403+P233	
P501	Dispose of contents/container in accordance with local/regional/nationa international regulations.
	(Contd. on page 3
	Conta. on page 3

Printing date 04/12/2016

Reviewed on 04/12/2016

#### Trade name: PROTEX SPRAY

(Contd. of page 2) · Classification system: · NFPA ratings (scale 0 - 4) Health = 1Fire = 4Reactivity = 3· HMIS-ratings (scale 0 - 4) HEALTH 1 Health = 1Fire = 4FIRE 4 **REACTIVITY** 3 Reactivity = 3 Other hazards Results of PBT and vPvB assessment · PBT: Not applicable. · vPvB: Not applicable. 3 Composition/information on ingredients · Chemical characterization: Mixtures · Description: Mixture of the substances listed below with nonhazardous additions. · Dangerous components: Reg.nr.: 01-2119475514-35-xxxx Hydrocarbons C6-C7, n-alkanes, iso-alkanes, 25-50% cyclenes, <5% n-hexane Flam. Liq. 2, H225; Asp. Tox. 1, H304; Aquatic Chronic 2, H411; Skin Irrit. 2, H315; STOT SE 3, H336; Aquatic Acute 2, H401 CAS: 106-97-8 butane 25-50% Reg.nr.: 01-2119474691-32 Flam. Gas 1, H220; Press. Gas, H280 CAS: 67-63-0 propan-2-ol 10-25% Reg.nr.: 01-2119457558-25 Flam. Lig. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336 CAS: 74-98-6 propane 5-10% Reg.nr.: 01-2119486944-21 Flam. Gas 1, H220; Press. Gas, H280 CAS: 108-21-4 isopropyl acetate 2.5-7.5% Reg.nr.: 01-2119537214-46 Flam. Liq. 2, H225; Eye Irrit. 2A, H319; STOT SE 3, H336

#### 4 First-aid measures

- · Description of first aid measures
- · General information: Immediately remove any clothing soiled by the product.
- · After inhalation:
- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly. • After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

- · Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

(Contd. on page 4)

le 4) —∪s

Printing date 04/12/2016

#### Reviewed on 04/12/2016

Trade name: PROTEX SPRAY

(Contd. of page 3) • Indication of any immediate medical attention and special treatment needed No further relevant information available.

#### 5 Fire-fighting measures

- · Extinguishing media
- · Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### 6 Accidental release measures

• Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.

• Environmental precautions: Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.

- *Methods and material for containment and cleaning up:* Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- Reference to other sections
  See Section 7 for information on safe handling.
  See Section 8 for information on personal protection equipment.
  See Section 13 for disposal information.

# 7 Handling and storage

#### · Handling:

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke.
   Demonstrand container, protect from container, and do not container.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- **Requirements to be met by storerooms and receptacles:** Observe official regulations on storing packagings with pressurized containers.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: Keep receptacle tightly sealed.
- · Storage class: 2 B
- · Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7. (Contd. on page 5) Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: PROTEX SPRAY

(Contd. of page 4) Control parameters Components with limit values that require monitoring at the workplace: The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits. 106-97-8 butane REL Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm TLV Short-term value: 2370 mg/m<sup>3</sup>, 1000 ppm 74-98-6 propane PEL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm REL Long-term value: 1800 mg/m<sup>3</sup>, 1000 ppm TLV refer to Appendix F inTLVs and BEIs book 108-21-4 isopropyl acetate PEL Long-term value: 950 mg/m<sup>3</sup>, 250 ppm TLV Short-term value: 836 mg/m<sup>3</sup>, 200 ppm Long-term value: 418 mg/m<sup>3</sup>, 100 ppm · Additional information: The lists that were valid during the creation were used as basis. · Exposure controls · Personal protective equipment: · General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Avoid contact with the eyes and skin. · Breathing equipment: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air. · Protection of hands: Protective gloves The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation · Material of gloves The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. · Penetration time of glove material The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed. (Contd. on page 6) US

Printing date 04/12/2016

Reviewed on 04/12/2016

# Trade name: PROTEX SPRAY

(Contd. of page 5)

• Eye protection: Safety glasses safety goggles

· Information on basic physical and	chemical properties
· General Information	
· Appearance:	
Form:	Liquefied gas
Color:	Colorless
· Odor:	Solvent-like
· Odor threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	-42 °C (-44 °F) (DIN EN ISO 3405)
· Flash point:	<-30 °C (<-22 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	365 °C (689 °F) (DIN 51794)
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
• Danger of explosion:	Product is not explosive. However, formation explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	1.5 Vol %
Upper:	12.0 Vol %
· Vapor pressure at 20 °C (68 °F):	2100 hPa (1575 mm Hg)
· Density at 20 °C (68 °F):	0.69 g/cm³ (5.758 lbs/gal) (ASTM D 4052)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not applicable.
Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
Partition coefficient (n-octanol/wat	er): Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
VOC content:	99.0 %
	683.4 g/l / 5.70 lb/gl

(Contd. on page 7)

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: PROTEX SPRAY

(Contd. of page 6)

### 10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

### 11 Toxicological information

- · Information on toxicological effects
- Acute toxicity:
- · Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization: No sensitizing effects known.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

67-63-0 propan-2-ol

· NTP (National Toxicology Program)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

### 12 Ecological information

#### · Toxicity

- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 1 (Self-classification according VwVwS, 17.05.1999): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

- Toxic for aquatic organisms
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.

(Contd. on page 8)

3

US

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2016

#### Reviewed on 04/12/2016

(Contd. of page 7)

#### Trade name: PROTEX SPRAY

- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation:
- Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

#### · Uncleaned packagings:

- · Recommendation:
- Disposal must be made according to official regulations.

Discharged containers can contain flammable or explosive vapours.

UN-Number DOT, ADR,ADN, IMDG, IATA	UN1950
UN proper shipping name	
DOT ADR/ADN	Aerosols, flammable 1950 Aerosols, ENVIRONMENTALLY
ADR/ADN	HAZARDOUS
IMDG	AEROSOLS (Naphtha (petroleum) hydrotreated light, isopentane), MARINE POLLUTANT
IATA	AEROSOLS, flammable
Transport hazard class(es)	
DOT	
Class	2.1
Label	2.1
ADR/ADN	
Class	2 5F Gases
Label	2.1
IMDG	
	2.1

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: PROTEX SPRAY

	(Contd. of page
Label	2.1
IATA	
Class	2.1
Label	2.1
Packing group DOT, ADR,ADN, IMDG, IATA	Void
Environmental hazards:	Product contains environmentally hazardo
<b></b>	substances:
Marine pollutant:	Yes Symbol (fich and trac)
Special marking (ADR/ADN):	Symbol (fish and tree) Symbol (fish and tree)
Special precautions for user	Warning: Gases
Danger code (Kemler):	-
EMS Number:	F-D,S-U
Stowage Code	SW1 Protected from sources of heat.
Segregation Code	SW22 For AEROSOLS with a maximu capacity of 1 litre: Category A. F- AEROSOLS with a capacity above 1 litr Category B. For WASTE AEROSOL- Category C, Clear of living quarters. SG69 For AEROSOLS with a maximu capacity of 1 litre: Segregation as for class Stow "separated from" class 1 except f division 1.4. For AEROSOLS with a capac. above 1 litre: Segregation as for th appropriate subdivision of class 2. F WASTE AEROSOLS: Segregation as for th appropriate subdivision of class 2.
Transport in bulk according to Annex MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
ADR/ADN	
Excepted quantities (EQ)	Code: E0 Not permitted as Excepted Quantity
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (ÉQ)	Code: E0 Not permitted as Excepted Quantity
UN "Model Regulation":	UN 1950 AEROSOLS, 2. ENVIRONMENTALLY HAZARDOUS

(Contd. on page 10)

# Safety Data Sheet

acc. to OSHA HCS

Printing date 04/12/2016

Reviewed on 04/12/2016

Trade name: PROTEX SPRAY

(Contd. of page 9)

#### 15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Sara
- Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

67-63-0 propan-2-ol

· TSCA (Toxic Substances Control Act):

- 106-97-8 butane
- 67-63-0 propan-2-ol
- 74-98-6 propane
- 108-21-4 isopropyl acetate
- 75-28-5 isobutane
- 78-78-4 isopentane
- · Proposition 65

· Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

67-63-0 propan-2-ol

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Abteilung Produktsicherheit

· Date of preparation / last revision 04/12/2016 / -

 Abbreviations and acronyms: Flam. Gas 1: Flammable gases – Category 1 Flam. Aerosol 1: Aerosols – Category 1 Press. Gas: Gases under pressure – Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

(Contd. on page 11)

A4

Printing date 04/12/2016

Reviewed on 04/12/2016

(Contd. of page 10)

US

#### Trade name: PROTEX SPRAY

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2