

# PRISMA ZX

## SAE 75W/90 GL-4+5

Synthetic performance gear oil for manual gearboxes and axle drives. API GL-4+5.

### Description

PRISMA ZX SAE 75W/90 is a synthetic gear oil for a multitude of uses. Guarantees optimum lubrication over a large temperature range, even under extreme conditions, both in synchronised and unsynchronised manual gearboxes in axles.

### Advantages

- optimum protection against wear
- excellent oxidation and shear stability
- good anti-foaming behaviour
- very low pour point
- excellent viscosity / temperature behaviour
- low pour point

### Field of application

PRISMA ZX SAE 75W/90 guarantees reliable lubrication in axle drives and end drives subject to high loads, while at the same time offering flawless functioning of manual gearbox synchronisation.

### Notes

Please adhere to the manufacturer's instructions.

### Specifications

API GL-4/5

### Safety + Performance

ZF TE-ML-07A; ZF TE-ML-08

### Technical data

Properties	Unit	Test according to	Values
Colour			yellow
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.872
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	84.2
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	14.7
Viscosity index		DIN ISO 2909	182
Flash point C.O.C.	°C	DIN EN ISO 2592	>220
Brookfield	°C / mPa·s	ASTM D 2983	-40 / 91000

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.