

# RACING GEAR OIL

SAE 10W/40

synthetic high-performance gear oil

## Description

High-performance gear oil. Exceptionally high pressure resistance. For separately lubricated gears and clutches. Highly efficient against clutch wear.

## Advantages

- synthetic (Synthetic Performance) with MC technology
- developed and used by MOTOREX Racing Support
- tested under the most extreme racing conditions
- optimal wear protection
- withstands maximum loads during races

## Field of application

MOTOREX GEAR OIL RACING PRO SAE 10W/40 is a gear oil for high-tech motorbikes – two and four-stroke – with separate lubrication. It guarantees maximum power with high gear protection at the same time – even under the hardest racing conditions.

## Technical data

Properties	Unit	Test according to	Values
Colour			brown
Density at 20 °C	g/cm <sup>3</sup>	ASTM D4052	0.854
Viscosity at 40 °C	mm <sup>2</sup> /s	DIN 51562-1	92.7
Viscosity at 100 °C	mm <sup>2</sup> /s	DIN 51562-1	14.2
Viscosity index		DIN ISO 2909	151
Pourpoint	°C	ASTM D5950	-36
Flash point C.O.C.	°C	DIN EN ISO 2592	>200
Brookfield	°C / mPas	ASTM D 2983	-26 / <150000

European waste code: 13 02 05 / Water hazard class: 1

The above information corresponds to the current state of our knowledge. We reserve the right to make changes. The performance characteristics indicated are based on testing and production tolerances standard in this industry. A safety data sheet is available.

04.05.17-FB19/MO2024-14

