

BEACON ADHESIVES COMPANY, INC.



Safety Data Sheet 29 CFR 1910.1200

Section 1: Company and Product Identification

Product Name: Beacon Slime Clear Glue

Product Code: Beacon Slime Clear Glue

Company: Beacon Adhesives Company, Inc.
125 MacQuesten Parkway South
Mount Vernon, NY 10550
PH: 914-699-3400

Emergency Response: Chem-Trec 1-800-424-9300

Section 2: Hazards Identification

GHS05

GHS05

GHS04

BLANK

Hazard Pictograms:

Hazard Class None

Hazard Statements: Precautionary Statements:

Precautionary Statements

P260: Do not breathe dust/fume/gas/mist/vapours/spray
P272: Contaminated work clothing should not be allowed out of the workplace
P264: Wash thoroughly after handling

P501: Dispose of contents/container in accordance with
local/regional/national/international rules.

Section 3: Composition / Information on Ingredients

Ingredient	%	Cas Number
Water	85	7732-18-5
Polyvinyl Alcohol	14.9	9002-89-5
Preservative	0.1	99-76-3
Total	100	

Section 4: First Aid Measures

If ingested: Rinse mouth. Seek immediate medical attention. Do not induce vomiting unless otherwise instructed. Never give anything by mouth to an unconscious person.

If inhaled: Remove to fresh air. Continuous breathing of vapors above molten material may cause irritation. If not breathing give artificial respiration. Immediate medical attention is required.

BEACON ADHESIVES COMPANY, INC.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses if present and easy to do. Get medical attention if irritation develops or persists.

Skin contact: Take off immediately all contaminated clothing. Rinse with water thoroughly. Get medical advice if irritation develops or persists.

Section 5: Fire Fighting Measures

Special Firefighting procedure Keep unnecessary personnel away. Fire fighters should wear full face SCBA and impervious protective clothing. Fire Fighters should avoid inhaling any combustion products.

Extinguishing Use Extinguishing measures appropriate to local circumstances and the surrounding environment.
Method / Equipment:

Flash Point >450 F

Section 6: Accidental Release Measures

Personal precautions, protective equipment and procedures: Wear appropriate personal protective equipment.

Containment Large Spills: Contain actively spilling material if safe and easy to do so. Dike the spilled material, where this is possible. Utilize absorbent clay or sand to contain and stop spreading
Equipment and Procedures: material.

Small Spills: Utilize absorbent clay or sand and transfer to waste receptacles.

Cleanup Procedures: Collect all contaminated clay, media, or other cleanup materials into a waste receptacle. Place in container for disposal with accordance with federal, state and local regulations.

Section 7: Handling and Storage

Safe Handling Precautions: No special precautions are necessary beyond normal good hygiene practices.

Recommendations for Storage: Keep container closed in a cool, dry and well ventilated place.

Section 8: Exposure Control / Personal Protection

General / Engineering Controls: Local exhaust ventilation should be utilized. Eye wash facilities must be available when handling this product.

Controls:

Work Clothing: Protective work clothing which covers skin and prevents exposures.

Eye/face protection: Wear safety goggles or face shield.

Skin Protection: Use good hygiene.

Respiratory Protection: Utilize respirator if airborne levels are not maintained below exposure limits, or if ventilation is inadequate.

BEACON ADHESIVES COMPANY, INC.

Additional Information: Observe good chemical hygiene practices. Do not smoke or eat while using this product. Wash hands or exposed skin after using the product.

Section 9: Physical and Chemical Properties

State: Liquid **Melting Point:** N/A **Freezing Point:** 32 F

Color: Clear **Boiling Point/Range:** 100 Deg C **pH:** 4.5 - 5.5

Sp Grav: 1.05 +/- **Odor:** N/A **Odor:** Typical

Flash Point: 450 Deg F

Upper Flam Limits: Not avail **Lower Flam Limits:** Not avail

Viscosity: 4,200 CPS

Section 10: Stability and Reactivity

General: This product is stable.

Conditions to avoid: Freezing Temperatures. Extremes of temperature

Hazardous Decomposition: Upon decomposition this product may yield oxides of nitrogen and ammonia, carbon dioxide, carbon monoxide and other low molecular weight hydrocarbon.

Section 11: Toxicological Information

Ingestion: Ingestion of product is unlikely. However, ingestion of product may produce gastrointestinal irritation or disturbances.

Skin Contact: May cause mild skin irritation. May cause allergic skin reaction in susceptible individuals.

Eye Contact: May cause mild irritation

Likely Routes of Exposure: Skin, inhalation, eyes

Exposure:

Toxicological Information (contained substances)

Hazardous substance (name)	LD50 Oral	LD50 Dermal	LC50 Inh	Irritancy:
None	No Info	No Info	No Info	None

Section 12: Ecological Information

General information: Product not Hazardous

Aquatic toxicity: N/A

Section 13: Disposal Information

Product disposal: Dispose of product in accordance with local, regional, and national regulations.

BEACON ADHESIVES COMPANY, INC.

Container disposal: Treat empty containers with extra care, recommending crushing containers.

Other considerations: No further information.

Section 14: Transport Information

DOT: Non-regulated

IMO/IMDG: Non-regulated

IATA: Non-regulated

OTHER: Inquire for further transport information.

Comments:

Section 15: Regulatory Information

TSCA: Not Listed

CERCLA RQ: Unlisted

SARA 311/312: Not Listed

SARA 313 Not Listed

Section 16: Other Information

SDS Author: Pete Ryan

Version Date: 07/07/2017

The information accumulated herein is based on data which Beacon Chemical Co., Inc. considers to be accurate; provided however, that the company makes no warranty as to the accuracy of the data. Anyone intending to use the information contained herein shall assume sole and complete responsibility for the results of said use including loss or damage resulting from the handling of the material (COMPANY DISCLAIMER...)