



**Particular attributes:**

- Soft
- Buffed and embossed furniture leather
- Strong finish
- Practical, smudge resistant and easy to maintain

**Type:** Pigmented leather

Size: 4.0 – 5.0 m<sup>2</sup>  
 Thickness: 0.9 – 1.1 mm

		<b>Requirements</b>	<b>Our test</b>
Colour fastness to light:	DIN EN ISO 105-B02	4	6
Colour fastness to rubbing*:	DIN EN ISO 11640		
	Dry 2000 rubs	4	4-5
	Wet 80 rubs	4	4-5
	Perspiration 50 rubs	4	4-5
Finish adhesion:	DIN EN ISO 1644/IUF 470	1,5	5,58
Tearing load:	DIN EN ISO 3377-1	20	33
Flexing endurance:	DIN EN ISO 5402-1 (Cracks)	20,000	50,000
Cigarette + Match test:	UNI EN 1021-1 and 2	-	Non-ignition

\*Sorensen test result shows the test result on the leather.

**Colour fastness to light:** The leather will become lighter as time passes. The light fastness indicates how soon this will appear on the leather. The light fastness is measured on a scale from 1 to 8 (1=lowest and 8=highest)

**Colour fastness to rubbing** is measured on a scale from 1 to 5 (1=lowest and 5=highest)

Technical specifications on the shade card are guideline only. The information may change due to changes in production. See website [www.sorensenleather.com](http://www.sorensenleather.com) which may be updated at any time with current technical specifications.

PCP: According to EU Council Directive 76/769/EEC

AZO dyes: According to EU Council Directive 76/769/EEC

Chrome VI: Our leather does not contain chrome VI

REACH: According to European Community Regulation on chemicals and their safe use (EC 1907/2006)

Sørensen logos and above information is trademark and copyright Sørensen Leather A/S, DENMARK

