FLOOR & FURNITURE REPAIR KIT INSTRUCTIONS

What's in your repair kit?

- 10 color repair compounds (white, black, red, yellow, blue, maple, oak, cherry, walnut, mahagony)
- Wood putty stick
- Spatula
- Brush
- Color mixing jar
- Your personal repair advisor available at support@coconix.com

WARNING!

Keep this product out of the reach of children! Do not ingest! Avoid contact with eyes! Only use as described! May irritate sensitive skin, it is recommended to use plastic gloves! Wash hands thoroughly with soap and water after use!

Step by step instructions

For best results, please visit our digital resource center for detailed instructions with repair videos, ebooks and more.



Visit go.coconix.com/woodrestore or scan the code!

1. Prepare the damaged area by carefully removing paint chips and wood splinters. Clean the area and remove any debris. Wipe it down with a damp cloth and let it dry thoroughly.

2. For damaged corners, cracks, holes or chips wider and deeper than 1/4 of an Inch, first use the wood putty to fill the gap. Cut off the required amount of wood putty and knead it to a uniform color. Apply within 2 minutes after kneading. Press product firmly until curing is noticeable. Do not leave a bulge. For a smooth surface, rub the area with a damp cloth prior to hardening. After 1 hour, wood putty can be sanded, tapped and drilled.

3. In case your repair requires a custom color, use our Color Mixing Guide to prepare the matching color repair compound mix in the empty mixing jar.

4. Apply the repair compound to the damaged area. First, apply it along the edges and work from the outside to the center to avoid air bubbles. Use the spatula for larger applications and the brush for surface applications and detail touch ups. Smooth out the surface and wipe off the excess with a paper towel.

5. Allow several hours to dry until the repair compound is no longer sticky to touch. If needed, apply additional layers until the repaired area is flush with the rest.

6. If you need help please email <u>support@coconix.com</u>. We have an awesome customer service team who lives and breathes this stuff.

FREQUENTLY ASKED QUESTIONS

The color mixture did not match my repair

We know that color matching can be challenging and our repair experts can help you get a perfect match. Email support@coconix.com with a picture of your repair project and we will give you personalized advice.

I am not sure if I need to use the wood putty

The wood putty is used for damaged corners, cracks, holes or chips wider and deeper than 1/4 of an Inch. Surface damages are not suitable for the wood putty. For surface damages, apply the repair compound directly. If you need help with your repair, email support@coconix.com with a picture of your repair project and we will give you personalized advice.

I made a mistake and want to start over

You can easily wipe off the repair compound with a paper towel or a wet cloth before it dries. If the repair compound is dry, firmly rub the area with hot soapy water and a cotton pad. Wood putty can be sanded, tapped and drilled after it dries.

The repair finish is too shiny or too matte

The correct sheen is almost as important as the correct color. For a matte finish, carefully rub the repaired area with a pad of steel wool to lower the sheen. For a glossy finish, you can apply varnish or clear lacquer over the repaired area.

I ran out of repair compound but my repair is not completed

Your repair kit includes 10 base colors to give you maximum flexibility to match any color, but we also want to minimize the waste. Although the repair compounds included in the kit are sufficient for most common repairs, every repair is unique. If you need more repair compound to complete your repair, please email support@coconix.com and we will help.

I have another problem

We are a small family business and we pride ourselves on outstanding customer service. We work so hard to make sure that every repair is completed to your satisfaction. If you have any problems with your repair kit, please email support@coconix.com and we'll make it right.

I would like to post a product review

We would love that too! Your review means the world to us. Thank you very much for taking the time. We hope we could make this an excellent experience for you. Go to <u>amazon.com/ryp</u> to post your review.



Your repair kit contains the most common colors needed for repair projects but for an exact match you might need to create a custom color mixture.

project.

2. Follow the grid in a horizontal line to the left to look up your main color.

look up your secondary color.

mixture.

6. Try your mixture on a small area and wait until it fully dries. Be patient and make small adjustments until the color matches just right.

7. Occassionally, you might need to mix three or more colors to achieve a perfect match. If you have any difficulties with color matching, please send us a picture of your repair project to support@coconix.com for personalized advice.

COLOR MIXING GUIDE

1. Use the color chart on the right side to identify the field that best represents the color of your repair

3. Follow the grid in a vertical line to the bottom to

4. Use the empty mixing jar to prepare your color mixture. Start your mixture with your main color. Gradually add your secondary color to the main color in the mixing jar until you get a correct match. Clean the spatula after each use and between color changes.

5. You can adjust the tint and shade by gradually adding white and black repair compound to your

Μ	V	NН										WH
A		BK									BK	
I		BL								BL		
N		RE							RE			
	ľ	YE						YE				
С	٢	MA					MA					
0	(OA				OA						
L	(СН			СН							
0	V	NA		WA								
R	Ν	мн	мн									
			МН	WA	СН	OA	MA	YE	RE	BL	BK	WH
		SECONDARY COLOR							R			

WH	WHITE	MA	MAPLE
ΒK	BLACK	OA	OAK
BL	BLUE	СН	CHERRY
RE	RED	WA	WALNUT
YE	YELLOW	ΜН	MAHAGONY

