

SPECIFICATIONS

ELECTRICAL	120V	
WATER CAPACITY	1.25 GAL	4.5 L
OPERATING PRESSURE	60 PSI	4.1 BAR
WATTAGE	1200W / 500W	
STEAM WAND STANDARD	3900IA - 8.5' steam hose	
OPTIONAL IRON	2100IR - 7' steam hose	
OPTIONAL STEAM BRUSH	3800IA - 8.5' steam hose	
POWER CONSUMPTION	17 amps, 20-amp plug required	
TANK CONSTRUCTION	Stainless steel	
LOW WATER INDICATOR	Standard	
STEAM CONNECTOR TYPE	Quick-release	
NET WEIGHT	19.5 lb (with wand)	8.6 kg (with wand)
SHIPPING WEIGHT	24.9 lb (with wand)	11.3 kg (with wand)
PRODUCT DIMENSIONS	13" x 8.5" x 15.75"	33 x 21.5 x 40 cm
SHIPPING DIMENSIONS	16" x 13" x 18"	40.6 x 33 x 45.7 cm
	16.2" x 4.5" x 4"	41 x 11.5 x 10 cm
ELECTRICAL APPROVAL	cETLus	
COUNTRY OF ORIGIN	Italy	
WARRANTY	Limited 1 year, Lifetime Tank	

6000BU-3900IA

DDOFFSSIONAL STEAM BOILED W/ HIGH DDFSSLIDE IDONING STEAM WAND

The 6000BU provides 60 PSI of steam pressure and up to 6 hours of continuous steam and is the fastest and most efficient way of delivering professional results. Paired with the 3900IA Ironing Steam Wand, it produces dry pressurized steam perfect for a wide variety of materials and applications.

Unlike a conventional steam iron, the 3900IA's unique ergonomic grip/handle can be used comfortably in any position, whether it's vertical like a steamer or horizontal like an iron. The aluminum soleplate provides more heat than our 3800IA brush and allows the user to press "nooks and cranny's" that would be challenging or impossible with a standard steam iron.

IT'S ALL ABOUT THE STEAM



BLOW DOWN VALVE



4 SAFETY SYSTEMS



PRESSURE GAUGE



MADE IN ITALY



ALUMINUM SOLEPLATE





THERMOSTAT



4.1 BAR PRESSURE

