

# **One-Step Clean**

#195-7115

770-424-3570

## **Description**

Remove ink residue and the stencil in One-Step in a dip tank. Concentrated new technology liquid you mix up to 6:1 with your water for removing direct emulsion, capillary film or direct/indirect system stencils. You decide the concentration. Soak in dip tank for a few minutes and the stencil falls off the mesh when you spray it out with water. Odor-free and we add degreaser so when you rinse, you are ready to coat.

#### **Benefits**

- Strong and works on all ink types.
- Last a long time
- Mesh safe.

Aggressiveness Index: Strength &

Odor: No Odor

## **Suggested Procedures**

- 1. Remove ink from the screen.
- 2. Place screen in dip tank with One-Step solution
- 3. Soak for 3 –5 minutes
- 4. Rinse thoroughly with high-pressure water.
- 5. Degrease before applying new stencil.

### **Disposal**

Drain - Considered drain safe into all sewer treatments.

# HMIS Ratings – 4-Extreme, 3-High, 2- Moderate, 1-Slight

1 Health 0 Flammability 0 Reactivity B Protection

Packaging: 5 gallon

# **Transportation Hazard Class**: Not regulated via UPS Ground

The technical data and information herein is believed to be accurate. It is offered for your consideration, investigation and verification. Buyer assumes all risk of use, storage and handling of the product. NO WARRANTY, expressed or implied is made, including, but not limited to, implied warranties of merchant ability and fitness for a particular purpose.

Revised: April 30, 2004