



**PW-485**

**Universal Press Wash**

**#195-8121**

### **Description**

Press wash for plastisol and graphic inks. No oily residues so tape sticks to your screen. Spray it directly on your stencil for speedy color changes and as a combination screen opener, platen cleaner, squeegee cleaner, or as a screen wash when saving the emulsion. May also be used in recirculation systems. Stencil safe.

### **Benefits**

- Dries fast at the press without oily residue.
- After a quick dry-buff, you can apply tape.
- Safe for solvent sensitive stencils.
- Very effective in recirculation systems.

**Aggressiveness Index: Strength** ★★

**Odor: Moderate-to-Strong Odor**

### **Suggested Procedures**

1. Use a separate brush for each chemical to avoid contamination.
2. Remove excess ink from the screen.
3. Spray PW-485 wherever there is ink.
4. Mix ink and PW-485 with scrub pad or brush.
5. Squeegee residue to one end and wipe clean with rags.

### **Disposal**

At the Press - Dispose of towels properly.

In The Recirculation System - Use a small squeegee to wipe excess PW-485 back into the sink.

**Not** drain safe. Must be properly disposed according to local codes and regulations.

### **HMIS Ratings – 4-Extreme, 3-High, 2- Moderate, 1-Slight**

1 Health      2 Flammability      0 Reactivity      P Protection

### **Packaging**

Gallon, 5 gallon, 55 gallon

### **Transportation Hazard Class**

Not regulated via UPS Ground

MSDS available - [www.lawsonsp.com](http://www.lawsonsp.com)

**Revised:** March 24, 2005