We Make It Simple. Trusted Since 1949





A Performance Cure

The Lawson M2-Encore combines color-blind, focused infrared heat with jet-air in a compact conveyor dryer. The M2-Encore is an energy-wise dryer that is simple-to-use, and is maintenance-free. It even ships fully assembled, ready-to-use. If you are starting a new business, need a second dryer or are just looking for a great value, this conveyor dryer is for you!

Trade-In, Trade-Up...YES! The Lawson M-2 Encore also cures the problem of out growing your dryer. Lawson guarantees you can Trade-In and Trade-Up your Lawson M2-Encore Dryer during your first 10 years of ownership.

Easy Installation. Made in the U.S.A. by Lawson.

Lawson's M2-Encore Provides:

- Exclusive Lawson Arrow Belt Tracking: The M2-Encore incorporates Lawson's exclusive Arrow Belt Tracking system - which means you'll never have to worry about keeping your dryer belt centered.
- ✓ Complete-Wrap Insulation: High-temperature, fiberglass insulation, specifically designed to keep heat in and your costs down. The entire heat chamber is wrapped including the end and bottom panels. We estimate a savings of 25-30 percent on your energy costs.
- ✓ Adjustable Zoned Heat Controls: Independent temperature controllers (percentage) allow you to individually adjust each "color-blind" I.R. panel as desired on all 8' models. Note: The Encore #3610 has 3 I.R. Elements and 1 master controller for the temperature.

ST. LOUIS | ATLANTA | NATIONWIDE





STANDARD FEATURES

- Adjustable Temperature Controls
- Independent Heat Zones (8' models)
- Jet-Air Recirculated
- Easy-Access/Hinged Heat Chamber
- Insulated Heat Chamber and Direct-Drive D.C. Motor
- Arrow Belt with 4-Point Belt Tracking
- Detachable Floor Legs
- Adjustable Entrance and Exit Doors
- · Black Memory Belt with Supports
- 220 Volts, 1-Phase
- National Safety Code Compliant/ETL
- One-Year Parts Warranty
- · Made in the U.S.A.

OPTIONAL FEATURES

- Custom In-Feed & Out-Feed
- 3-Phase Wiring
- Export Electrics
- Crating







M2-ENCORE CONVEYOR DRYER	2408	2410	3608	3610	4810
Estimated Max. Production	260+*	390+*	390+*	520+*	950+
Overall Length	8'	10'	8'	10'	10'
Overall Width	38"	38"	50"	50"	62"
Belt Width	24"	24"	36"	36"	48"
Overall Height (floor to top)	48"	48"	48"	48"	48"
Heat Chamber Length	4'	6'	4'	6'	6'
In-Feed	2'	2'	2'	2'	2'
Out-Feed	2'	2'	2'	2'	2'
Belt Height	34"	34"	34"	34"	34"
Jet-Air CFM	300	600	320	600	600
Air Zones	1	2	1	2	2
Flue Size	6"	6"	8"	8"	8"
Heat Panels	2	3	2	3	3
Max Heater Wattage	6000	9000	9000	13500	18000
Heater Length	24"	24"	36"	36"	48"
AMPS: 230 volt, Single Phase, 3 wires + grnd	26	40	40	58	
Est. Crated Weight - Ibs	800	1,000	1,000	1,200	
Est. Crate Size (W x L x H)	48"x110"x48"	48"x156"x48"	60"x110"x48"	60"x156"x48"	72"x156"x48"



