

### **ACOUSTIC FLOORING**

# dB FFR Resilient Layer 6mm





### COST EFFECTIVE IMPACT PRODUCT

dB FFR Resilient Underlay is a fully recycled rubber designed for use with both soft and hard flooring, such as Engineered timber, Laminate, stone flooring and carpet, designed to absorb footfall noise and increase living standards within the construction, whether in residential or commercial applications. The material also has a Zero OPD (Ozone Depleting Potential) and Zero GWP (Global Warming Potential).

The specially selected Rubber particles and fibres are designed to give excellent resilience yet upmost compressive strength.

<b>√</b>	Impact Rating	41 dB L <sub>nTw</sub>
)))	Airborne Rating	51 dB D <sub>nTw</sub> +C <sub>tr</sub>
	Thickness	6mm
	Sheet Dimensions	1.25m x 10m
K M K M	Area	12.5m <sup>2</sup>
ශීන	Eco Product	Yes

All test data is site test data with suitable ceiling treatments & flanking paths removed. For more construction details for the test results please contact the office.

# SUITABLE FOR USE IN











HOME

WORK

LEISURE EDUCATION HEALTH

# **FEATURES**

- Easy to install
- Unlike cheaper foams, remains continually elastic
- Fully recycled
- **Cost effective**
- Suitable under hard surfacing and carpet
- Ocument E (England & Wales) Section 5 (Scotland) and PartG (Northern Ireland) compliant
- Suitable on timber and concrete floors
- Suitable for Refurbishment & New Build
- Good footfall noise reduction
- Good therrnal conductivity
- Minimum construction low floor build-up

"This is an easy to lay product that is cost effective." The team at Sound Insulation Store

**Telephone** 01928 571 856

Email hello@soundinsulationstore.co.uk

www.soundinsulationstore.co.uk

Sound Insulation Store Unit 4 Boleyn Court, Manor Park Industrial Estate Runcorn, WA7 ISR