

HIGH LEVEL AIRBORNE AND IMPACT






dB Matting 15 is a high performing acoustic floor product to be used in Residential, Commercial and Industrial projects. The dB Matting range has been uniquely engineered to reduce both impact and airborne sound when laid over a structure.

When used in the correct application, dB Matting 15 can be installed over timber, concrete and screeded floors with lath and plaster, suspended timber/metal ceilings or Resilient Bar ceilings to ensure compliance to all UK Building Regulations.

	Impact Rating	47 dB L_{nTw}
	Airborne Rating	58 dB $D_{nTw} + C_{tr}$
	Thickness	15mm
	Sheet Dimensions	1.25m x 1m
	Area	1.25m ²
	Eco Product	Yes

All test data is site test data with suitable ceiling treatments & flanking paths removed. For more construction details for the test results please contact the office.

FEATURES

-  Meets Part E of the Building Regulations for BOTH airborne and impact noise
-  Improves airborne sound insulation
-  Simply laid under most floor finishes
-  Easily cut and shaped
-  Suitable for over timber or concrete floor structures

SUITABLE FOR USE IN



HOME



WORK



LEISURE



EDUCATION



HEALTH

“ This is a very popular underlay product for both refurbishment & new build projects due to the weight, performance and ease of installation. We see this as a great quick fix solution to increase the performance of any floor and reduce the need to uplift existing floor boards etc.”

The team at Sound Insulation Store

Telephone 01928 571 856
Email hello@soundinsulationstore.co.uk

www.soundinsulationstore.co.uk

Sound Insulation Store
Unit 4 Boleyn Court,
Manor Park Industrial Estate
Runcorn, WA7 1SR