


HIGH LEVEL SELLING PANEL

dB Panel 28 has been designed as a versatile impact reducing floor panel that can be used as a structural or an overlay board.



When used as an overlay board the acoustic felt resilient layer can take care of minor undulations of the floor surface.

The product consists of 18mm chipboard bonded to a 10mm acoustic felt. dB Panel has a tongue and groove edge and is installed as a floating floor with no mechanical fixings through the floor.

| | | |
|--|------------------|--------------------------|
|  | Impact Rating | 55 dB L_{nTw} |
|  | Airborne Rating | 55 dB $D_{nTw} + C_{tr}$ |
|  | Thickness | 28mm |
|  | Sheet Dimensions | 2.4m x 0.6m |
|  | Area | 1.44m ² |

All test data is site test data with suitable ceiling treatments & flanking paths removed. For more construction details for the test results please contact the office.

FEATURES

-  Versatile and economical
-  Refurbishment and New Build
-  Compatible with a range of dB Systems
-  Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)
-  Robust Details FFT5 compliant for floor structures EFC-1, EFC-2 and EFS-1
-  Ideal for ceramic tiling in conjunction with Permalayer
-  Easy to install in a single time saving operation
-  A peel clean version is now available to allow for spotless handovers

SUITABLE FOR USE IN



HOME



WORK



LEISURE



EDUCATION



HEALTH

Telephone 01928 571 856
Email hello@soundinsulationstore.co.uk

www.soundinsulationstore.co.uk

Sound Insulation Store
Unit 4 Boleyn Court,
Manor Park Industrial Estate
Runcorn, WA7 1SR