



HIGH PERFORMANCE PANEL




dB Panel 33 is our acoustic floor board panel designed for timber frame developments.

The combination of acoustic felt, rubber and chipboard gives a high level of acoustic performance for both airborne and impact and perform to all UK Building Regulations Requirements whether this be Approved Document E (England & Wales), Section 5 (Scotland) or Part G (Northern Ireland).

	Impact Rating	48 dB L_{nTw}
	Airborne Rating	56 dB $D_{nTw} + C_{tr}$
	Thickness	33mm
	Sheet Dimensions	2.4m x 0.6m
	Area	1.44m ²

All test data is site test data with suitable ceiling treatments & flanking paths removed. For more construction details for the test results please contact the office.

FEATURES

-  Versatile and economical
-  Suitable for New Build, Change of Use and Refurbishment Projects
-  Compatible with a range of dB Systems
-  Building Regulations Part E (England and Wales), Section 5 (Scotland) and Part G (Northern Ireland)
-  Can achieve Robust Details Performance levels on timber frame development
-  Easy to install in a single time saving operation
-  A peel clean version is now available to allow for spotless handovers

SUITABLE FOR USE IN



HOME



WORK



LEISURE



EDUCATION



HEALTH

Telephone 01928 571 856
Email hello@soundinsulationstore.co.uk

www.soundinsulationstore.co.uk

Sound Insulation Store
Unit 4 Boleyn Court,
Manor Park Industrial Estate
Runcorn, WA7 1SR