

Vertus CLA604A Line Array

Extruded-aluminium powder-coated cabinets. Superior as well as inferior latching system, enables the extension of the length of the line array adding CLA604A modules for a greater modularity of the system

Possibility to angle the columns of +/- 30 degrees on a horizontal plane

Ideal for both live applications, assisted by the CLA 208SA active subwoofer, as well as for fixed installation

Easily expandable for a total power of 6600W (stereo system composed of 3 x CLA608A and 3 x CLA208SA)

Very light and easy to carry

High-level sound quality from 50Hz to 20kHz expressly developed for live performance

Long distance sound projection and better SPL distribution towards the audience

Great and dynamic power performance thanks to tri-amplification system

Lightweight and easy to carry

Design and elegance for an easy integration even in the most demanding installations

Very compact dimensions enable the listener to concentrate on sound and not on speakers!

High horizontal dispersion

Configuration 2-way

Built-in amplifier cont. rms LF/HF W 350/80

Built-in amplifier max. rms LF/HF W 400/100

Built-in amplifier max. peak LF/HF W 800/200

Frequency response @-6dB 130Hz - 20KHz

Low frequency woofer inch 6 x 4" - 1" coil

High frequency driver inch 4 x 1" - 1" coil

Maximum SPL cont/peak dB 122 / 125

Dispersion H x V 100° x 20°

Input impedance kOhm 22

Crossover frequency kHz 2.5

AC Power requirements VA 450

Input connectors XLR with loop

Power cord m/inch 5 / 16.4

Net dimensions (WxHxD) mm 130x841x130 Net weight kg 9

Transport dimensions (WxHxD) mm 220x930x220

Transport weight kg/lb 11.5 / 25.35