

Fuseless motor starter Direct start 600VAC Size S00 0.7-1A  
220/240VAC 50/60HZ screw connection For screw mounting Or 35  
mm rail-mounting Type of coordination 2 IQ = 150 KA Also full fills  
type Of coordination 1 1NO (contactor)

|  |                               |
|--|-------------------------------|
| <b>Product brand name</b>  | SIRIUS                        |
| <b>Product designation</b>   | non-fused motor starter 3RA2  |
| <b>Design of the product</b>   | direct starter                |
| <b>Manufacturer's article number</b>   |                               |
| <ul style="list-style-type: none"> <li>• of the supplied contactor</li> </ul>        | <a href="#">3RT2015-1AP61</a> |
| <ul style="list-style-type: none"> <li>• of the supplied circuit-breakers</li> </ul> | <a href="#">3RV2011-0JA10</a> |
| <ul style="list-style-type: none"> <li>• of the supplied link module</li> </ul>      | <a href="#">3RA1921-1DA00</a> |

### General technical data

|  |            |
|--|------------|
| <b>Size of the circuit-breaker</b>   | S00        |
| <b>Size of load feeder</b>   | S00        |
| <b>Product extension</b>   |            |
| <ul style="list-style-type: none"> <li>• Auxiliary switch</li> </ul>                             | Yes        |
| <b>Insulation voltage</b>  |            |
| <ul style="list-style-type: none"> <li>• with degree of pollution 3 at AC rated value</li> </ul> | 690 V      |
| <b>Degree of pollution</b>   | 3          |
| <b>Surge voltage resistance rated value</b>  | 6 kV       |
| <b>Protection class IP</b>   |            |
| <ul style="list-style-type: none"> <li>• on the front</li> </ul>                                 | IP20       |
| <ul style="list-style-type: none"> <li>• of the terminal</li> </ul>                              | IP00       |
| <b>Shock resistance</b>  |            |
| <ul style="list-style-type: none"> <li>• acc. to IEC 60068-2-27</li> </ul>                       | 6g / 11 ms |
| <b>Mechanical service life (switching cycles)</b>  |            |
| <ul style="list-style-type: none"> <li>• of contactor typical</li> </ul>                         | 30 000 000 |
| <b>Type of assignment</b>  | 2          |

### Main circuit

|   |                   |
|---|-------------------|
| <b>Number of poles for main current circuit</b>                                   | 3                 |
| <b>Design of the switching contact</b>  | electromechanical |
| <b>Adjustable pick-up value current of the current-dependent overload release</b> | 0.7 ... 1 A       |
| <b>Operating voltage</b>  |                   |
| <ul style="list-style-type: none"> <li>• rated value</li> </ul>                   | 690 V             |
| <ul style="list-style-type: none"> <li>• at AC-3 rated value maximum</li> </ul>   | 690 V             |
| <b>Operating frequency rated value</b>  | 50 ... 60 Hz      |
| <b>Operating current</b>  |                   |

|  |   |
|--|---|
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> </ul> </li> </ul>  | 0.85 A  |
| <b>Operating power</b>   |   |
| <ul style="list-style-type: none"> <li>• at AC-3 <ul style="list-style-type: none"> <li>— at 400 V rated value</li> <li>— at 500 V rated value</li> <li>— at 690 V rated value</li> </ul> </li> </ul>      | 250 W<br>370 W<br>550 W   |
| <b>Control circuit/ Control</b>  |   |
| <b>Control supply voltage at AC</b>  |   |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul>                                   | 220 V<br>187 ... 242 V<br>240 V<br>192 ... 264 V                      |
| <b>Apparent holding power of magnet coil at AC</b>   | 4.8 V·A   |
| <b>Inductive power factor with the holding power of the coil</b>   | 0.25  |
| <b>Auxiliary circuit</b>   |   |
| <b>Number of NC contacts for auxiliary contacts</b>  | 0   |
| <b>Number of NO contacts for auxiliary contacts</b>  | 1   |
| <b>Protective and monitoring functions</b>   |   |
| <b>Trip class</b>  | CLASS 10  |
| <b>Design of the overload release</b>  | thermal (bimetallic)  |
| <b>Response value current</b>  |   |
| <ul style="list-style-type: none"> <li>• of instantaneous short-circuit trip unit</li> </ul>   | 13 A  |
| <b>UL/CSA ratings</b>  |   |
| <b>Yielded mechanical performance [hp]</b>   |   |
| <ul style="list-style-type: none"> <li>• for three-phase AC motor <ul style="list-style-type: none"> <li>— at 575/600 V rated value</li> </ul> </li> </ul>   | 0.5 hp  |
| <b>Short-circuit protection</b>  |   |
| <b>Product function Short circuit protection</b>   | Yes   |
| <b>Design of the short-circuit trip</b>  | magnetic  |
| <b>Conditional short-circuit current (I<sub>q</sub>)</b>   |   |
| <ul style="list-style-type: none"> <li>• at 690 V acc. to IEC 60947-4-1 rated value</li> <li>• at 400 V acc. to IEC 60947-4-1 rated value</li> <li>• at 500 V acc. to IEC 60947-4-1 rated value</li> </ul> | 100 000 A<br>153 000 A<br>100 000 A                                   |
| <b>Installation/ mounting/ dimensions</b>  |   |
| <b>Mounting position</b>   | vertical  |
| <b>Mounting type</b>   | Snap-mounted to DIN rail or screw-mounted with additional push-in lug |
| <b>Height</b>  | 167.2 mm  |

|  |         |
|--|---------|
| <b>Width</b>   | 45 mm   |
| <b>Depth</b>   | 97.1 mm |
| <b>Required spacing</b>  |         |
| <ul style="list-style-type: none"> <li>• for grounded parts <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— Backwards 0 mm</li> <li>— upwards 20 mm</li> <li>— at the side 9 mm</li> <li>— downwards 10 mm</li> </ul> </li> <li>• for live parts <ul style="list-style-type: none"> <li>— forwards 0 mm</li> <li>— Backwards 0 mm</li> <li>— upwards 20 mm</li> <li>— downwards 10 mm</li> <li>— at the side 9 mm</li> </ul> </li> </ul> |         |

### Connections/ Terminals

|  |                      |
|--|----------------------|
| <b>Type of electrical connection</b>   |                      |
| <ul style="list-style-type: none"> <li>• for main current circuit</li> </ul>   | screw-type terminals |
| <b>Type of connectable conductor cross-sections</b>  |                      |
| <ul style="list-style-type: none"> <li>• for main contacts <ul style="list-style-type: none"> <li>— stranded 0.5 ... 4 mm<sup>2</sup>, 2x (0.75 ... 2.5 mm<sup>2</sup>)</li> </ul> </li> <li>• at AWG conductors for main contacts 2x (20 ... 16), only for contactor 2x (18 ... 14), 2x 12</li> </ul> |                      |
| <b>Connectable conductor cross-section for main contacts</b>   |                      |
| <ul style="list-style-type: none"> <li>• finely stranded with core end processing 0.5 ... 2.5 mm<sup>2</sup></li> </ul>  |                      |

### Safety related data

|  |  |
|--|--|
| <b>B10 value</b>   |  |
| <ul style="list-style-type: none"> <li>• with high demand rate acc. to SN 31920 1 000 000</li> </ul> |  |
| <b>Proportion of dangerous failures</b>  |  |
| <ul style="list-style-type: none"> <li>• with high demand rate acc. to SN 31920 73 %</li> </ul>      |  |

### Certificates/ approvals

|                          |                                |                           |
|--------------------------|--------------------------------|---------------------------|
| General Product Approval | For use in hazardous locations | Declaration of Conformity |
|--------------------------|--------------------------------|---------------------------|



[Miscellaneous](#)

|                   |                   |
|-------------------|-------------------|
| Test Certificates | Marine / Shipping |
|-------------------|-------------------|

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



|                   |       |         |
|-------------------|-------|---------|
| Marine / Shipping | other | Railway |
|-------------------|-------|---------|



[Confirmation](#)

[Vibration and Shock](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RA2110-0JA15-1AP6>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RA2110-0JA15-1AP6>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2110-0JA15-1AP6>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RA2110-0JA15-1AP6&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RA2110-0JA15-1AP6&lang=en)

**Characteristic: Tripping characteristics, I<sup>2</sup>t, Let-through current**

<https://support.industry.siemens.com/cs/ww/en/ps/3RA2110-0JA15-1AP6/char>

**Further characteristics (e.g. electrical endurance, switching frequency)**

<http://www.automation.siemens.com/bilddb/index.aspx?view=Search&mlfb=3RA2110-0JA15-1AP6&objecttype=14&gridview=view1>



**last modified:**

03/05/2020