

Coupling relay in industrial enclosure 3 changeover contacts Wide voltage range 24 V to 240 V AC/DC Spring-type terminals



Product brand name	SIRIUS
Product designation	Coupling relay in industrial enclosure
Product type designation	3RQ2

General technical data

Consumed active power	5 W
Insulation voltage <ul style="list-style-type: none"> • for overvoltage category III according to IEC 60664 — with degree of pollution 3 rated value 	300 V
Degree of pollution	3
Surge voltage resistance rated value	4 kV
maximum permissible voltage for safe isolation <ul style="list-style-type: none"> • between auxiliary and auxiliary circuit • between control and auxiliary circuit acc. to IEC 60947-1 	300 V 300 V
Protection class IP	IP20
Shock resistance <ul style="list-style-type: none"> • acc. to IEC 60068-2-27 • for railway applications acc. to DIN EN 61373 	11g / 15 ms Category 1, Class B

Vibration resistance	
<ul style="list-style-type: none"> • acc. to IEC 60068-2-6 • for railway applications acc. to DIN EN 61373 	10 ... 55 Hz: 0.35 mm Category 1, Class B
Switching behavior	monostable
Mechanical service life (switching cycles)	
<ul style="list-style-type: none"> • typical 	10 000 000
Electrical endurance (switching cycles)	
<ul style="list-style-type: none"> • at AC-15 at 230 V typical 	100 000
Thermal current of the switching element with contacts maximum	5 A
Reference code acc. to DIN EN 81346-2	K

Control circuit/ Control

Control supply voltage 1 at AC	
<ul style="list-style-type: none"> • at 50 Hz • at 60 Hz 	24 ... 240 V 24 ... 240 V
Control supply voltage 1	
<ul style="list-style-type: none"> • at DC 	24 ... 240 V
Operating range factor control supply voltage rated value at DC	
<ul style="list-style-type: none"> • initial value • Full-scale value 	0.7 1.1
Operating range factor control supply voltage rated value at AC at 50 Hz	
<ul style="list-style-type: none"> • initial value • Full-scale value 	0.7 1.1
Operating range factor control supply voltage rated value at AC at 60 Hz	
<ul style="list-style-type: none"> • initial value • Full-scale value 	0.7 1.1
Switch-on delay time	
<ul style="list-style-type: none"> • at AC maximum • at DC maximum 	10 ms 10 ms
Off-delay time	100 ms
Design of the relay operating mechanism	poled
Product component Plug-in socket	No

Short-circuit protection

Design of the fuse link	
<ul style="list-style-type: none"> • for short-circuit protection of the auxiliary switch required 	fuse gL/gG: 6 A

Auxiliary circuit

Material of switching contacts	AgSnO2
Number of NC contacts for auxiliary contacts	0

Number of NO contacts for auxiliary contacts	0
Number of CO contacts	
• for auxiliary contacts	3
Contact reliability of auxiliary contacts	one incorrect switching operation of 100 million switching operations (17 V, 5 mA)
Type of voltage	AC/DC

Outputs

Ampacity of the output relay at AC-15	
• at 24 V at 50/60 Hz	3 A
• at 110 V at 50/60 Hz	3 A
• at 250 V at 50/60 Hz	3 A
Ampacity of the output relay at DC-13	
• at 24 V	1 A
• at 125 V	0.2 A
• at 250 V	0.1 A

Electromagnetic compatibility

EMC emitted interference	
• acc. to IEC 60947-1	ambience A (industrial sector)
EMI immunity	
• acc. to IEC 60947-1	corresponds to degree of severity 3
Conducted interference	
• due to burst acc. to IEC 61000-4-4	2 kV
• due to conductor-earth surge acc. to IEC 61000-4-5	2 kV (line to ground)
• due to conductor-conductor surge acc. to IEC 61000-4-5	1 kV (line to line)
Field-bound parasitic coupling acc. to IEC 61000-4-3	10 V/m
Electrostatic discharge acc. to IEC 61000-4-2	4 kV contact discharging, 8 kV air discharging

Safety related data

Electromagnetic compatibility	IEC 60947-1 / IEC 61000-6-2 / IEC 61000-6-4
--------------------------------------	---

Connections/ Terminals

Product function	
• removable terminal for auxiliary and control circuit	Yes
Type of electrical connection	Push-in terminal
Type of connectable conductor cross-sections	
• solid	0.5 ... 4 mm ²
• finely stranded with core end processing	0.5 ... 2.5 mm ²
• at AWG conductors solid	20 ... 12
Connectable conductor cross-section	
• solid	0.5 ... 4 mm ²

<ul style="list-style-type: none"> finely stranded with core end processing finely stranded without core end processing 	<p>2.5 mm²</p> <p>0.5 mm²</p>
AWG number as coded connectable conductor cross section <ul style="list-style-type: none"> solid stranded 	<p>12 ... 20</p> <p>12 ... 20</p>
Wire stripping length of the cable <ul style="list-style-type: none"> for auxiliary and control contacts 	<p>10 mm</p>

Installation/ mounting/ dimensions

Mounting position	any
Mounting type	screw and snap-on mounting onto 35 mm standard mounting rail
Height	100 mm
Width	22.5 mm
Depth	90 mm

Ambient conditions

Installation altitude at height above sea level <ul style="list-style-type: none"> maximum 	<p>2 000 m</p>
Relative humidity <ul style="list-style-type: none"> during operation 	<p>10 ... 95 %</p>

Certificates/ approvals

General Product Approval	EMC	Declaration of Conformity
 <p>CCC</p>	 <p>CSA</p>	 <p>UL</p>
  		
<p>EG-Konf.</p>		

Declaration of Conformity	Test Certificates	other	Railway
Miscellaneous	Type Test Certificates/Test Report	Confirmation	Confirmation


Further information


Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RQ2000-2CW00>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RQ2000-2CW00>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3RQ2000-2CW00>





last modified:

04/04/2020