

Illuminated pushbutton, 22 mm, round, plastic, green, pushbutton, flat, momentary contact type, with holder, 1 NO, LED module with integrated LED 24 V AC/DC, Spring-type terminal



|  |  |
|--|--|
| <b>Product brand name</b>  | SIRIUS ACT   |
| <b>Product designation</b>   | Illuminated pushbuttons  |
| <b>Design of the product</b>   | Complete unit  |
| <b>Product type designation</b>  | 3SU1   |
| <b>Product line</b>  | Plastic, black, 22 mm  |
| <b>Manufacturer's article number</b>   |  |
| <ul style="list-style-type: none"> <li>• 1 of supplied contact module</li> <li>• of supplied LED module</li> <li>• of the supplied holder</li> <li>• of the supplied actuator</li> </ul> | <a href="#">3SU1400-1AA10-3BA0</a><br><a href="#">3SU1401-1BB40-3AA0</a><br><a href="#">3SU1500-0AA10-0AA0</a><br><a href="#">3SU1001-0AB40-0AA0</a> |
| <b>Number of command points</b>  | 1  |

| Actuator   |                        |
|--|------------------------|
| <b>Design of the operating mechanism</b>                                     | Button, flat           |
| <b>Manner of function of the actuating element</b>                           | momentary contact type |
| <b>Product extension optional Light source</b>                               | Yes                    |
| <b>Color</b>   |                        |
| <ul style="list-style-type: none"> <li>• of the actuating element</li> </ul> | green                  |
| <b>Material of the actuating element</b>                                     | plastic                |
| <b>Shape of the actuating element</b>  | round                  |

|   |  |
|---|--|
| Outer diameter of the actuating element                 | 29.45 mm   |
| Number of contact modules                               | 1  |
| <b>Front ring</b>                                       |  |
| Product component front ring                            | Yes  |
| Design of the front ring                                | Standard   |
| Material of the front ring                              | plastic  |
| Color of the front ring                                 | black  |
| <b>Holder</b>   |  |
| Material of the holder                                  | Plastic  |
| <b>Display</b>  |  |
| Number of LED modules                                   | 1  |
| <b>General technical data</b>                           |  |
| <b>Product function</b>                                 |  |
| • positive opening                                      | No   |
| <b>Product component</b>                                |  |
| • Light source  | Yes  |
| <b>Insulation voltage</b>                               |  |
| • rated value   | 320 V  |
| <b>Degree of pollution</b>                              | 3  |
| <b>Type of voltage</b>                                  |  |
| • of the operating voltage                              | AC/DC  |
| <b>Surge voltage resistance rated value</b>             | 4 kV   |
| <b>Protection class IP</b>                              | IP66, IP67, IP69(IP69K)                              |
| • of the terminal                                       | IP20   |
| <b>Degree of protection NEMA rating</b>                 | 1, 2, 3, 3R, 4, 4X, 12, 13                           |
| <b>Shock resistance</b>                                 |  |
| • acc. to IEC 60068-2-27                                | Sinusoidal half-wave 50 g / 11 ms                    |
| • for railway applications acc. to DIN EN 61373         | Category 1, Class B                                  |
| <b>Vibration resistance</b>                             |  |
| • acc. to IEC 60068-2-6                                 | 10 ... 500 Hz: 5g                                    |
| • for railway applications acc. to DIN EN 61373         | Category 1, Class B                                  |
| <b>Operating frequency maximum</b>                      | 3 600 1/h  |
| <b>Mechanical service life (switching cycles)</b>       |  |
| • typical   | 3 000 000  |
| <b>Electrical endurance (switching cycles)</b>          |  |
| • typical   | 10 000 000   |
| <b>Thermal current</b>                                  | 10 A   |
| <b>Reference code acc. to DIN EN 81346-2</b>            | S  |
| <b>Reference code acc. to DIN EN 61346-2</b>            | S  |
| <b>Continuous current of the C characteristic MCB</b>   | 10 A; for a short-circuit current smaller than 400 A |
| <b>Continuous current of the quick DIAZED fuse link</b> | 10 A   |

|   |   |
|---|---|
| <b>Continuous current of the DIAZED fuse link gG</b>  | 10 A                                      |
| <b>Operating voltage</b>  |   |
| <ul style="list-style-type: none"> <li>• at AC <ul style="list-style-type: none"> <li>— at 50 Hz rated value</li> <li>— at 60 Hz rated value</li> </ul> </li> <li>• at DC <ul style="list-style-type: none"> <li>— rated value</li> </ul> </li> </ul> | 5 ... 500 V<br>5 ... 500 V<br>5 ... 500 V |

### Power Electronics

|                            |  |
|----------------------------|--|
| <b>Contact reliability</b> | One maloperation per 100 million (17 V, 5 mA), one maloperation per 10 million (5 V, 1 mA) |
|----------------------------|--|

### Supply voltage

|  |              |
|--|--------------|
| <b>Type of voltage of the supply voltage</b>   |              |
| <ul style="list-style-type: none"> <li>• of the light source</li> </ul>                                  | AC/DC        |
| <b>Supply voltage of the light source at AC</b>  |              |
| <ul style="list-style-type: none"> <li>• at 50 Hz rated value</li> <li>• at 60 Hz rated value</li> </ul> | 24 V<br>24 V |
| <b>Supply voltage of the light source at DC</b>  |              |
| <ul style="list-style-type: none"> <li>• rated value</li> </ul>  | 24 V         |

### Control circuit/ Control

|   |     |
|---|-----|
| <b>Inrush current of LED module maximum</b> | 2 A |
|---|-----|

### Auxiliary circuit

|   |              |
|---|--------------|
| <b>Design of the contact of auxiliary contacts</b>  | Silver alloy |
| <b>Number of NC contacts for auxiliary contacts</b> | 0            |
| <b>Number of NO contacts for auxiliary contacts</b> | 1            |

### Connections/ Terminals

|   |   |
|---|---|
| <b>Type of electrical connection</b>  |   |
| <ul style="list-style-type: none"> <li>• of modules and accessories</li> </ul>  | Spring-type terminal  |
| <b>Type of connectable conductor cross-sections</b>   |   |
| <ul style="list-style-type: none"> <li>• solid without core end processing</li> <li>• finely stranded with core end processing</li> <li>• finely stranded without core end processing</li> <li>• at AWG conductors</li> </ul> | 2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (0.25 ... 0.75 mm <sup>2</sup> )<br>2x (0.25 ... 1.5 mm <sup>2</sup> )<br>2x (24 ... 16) |
| <b>Tightening torque of the screws in the bracket</b>   | 1 ... 1.2 N·m   |

### Lamp

|                                  |                   |
|----------------------------------|-------------------|
| <b>Type of light source</b>      | LED               |
| <b>Color of the light source</b> | green             |
| <b>Light intensity</b>           | 900 ... 1 800 mcd |

### Ambient conditions

|  |                |
|--|----------------|
| <b>Ambient temperature</b>   |                |
| <ul style="list-style-type: none"> <li>• during operation</li> </ul> | -25 ... +70 °C |

- during storage

-40 ... +80 °C

Environmental category during operation acc. to IEC 60721

3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95 %, no condensation in operation permitted for all devices behind front panel)

### Installation/ mounting/ dimensions

|  |                      |
|--|----------------------|
| <b>Mounting type</b>                               | front panel mounting |
| • of modules and accessories                       | Front plate mounting |
| <b>Height</b>                                      | 40 mm                |
| <b>Width</b>                                       | 30 mm                |
| <b>Shape of the installation opening</b>           | round                |
| <b>Mounting diameter</b>                           | 22.3 mm              |
| <b>Positive tolerance of installation diameter</b> | 0.4 mm               |
| <b>Mounting height</b>                             | 11 mm                |
| <b>Installation width</b>                          | 29.5 mm              |
| <b>Installation depth</b>                          | 49.7 mm              |

### Certificates/ approvals

#### General Product Approval

#### Declaration of Conformity



[Miscellaneous](#)

#### Test Certificates

#### Marine / Shipping

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)



#### Marine / Shipping

#### other



[Confirmation](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**


<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1102-0AB40-3BA0>


**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1102-0AB40-3BA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1102-0AB40-3BA0>





last modified:

03/10/2020