

Electronics module IO-Link for ID key-operated switch, freely-programmable electronic switches, controller and RFID authentication of the switching function, black, operating voltage 24 V DC, screw terminal, for front plate mounting, for industrial application in control cabinets and machines

<b>Product brand name</b>	SIRIUS ACT
<b>Product designation</b>	Electronic module for ID key-operated switches
<b>Product type designation</b>	3SU1

### Actuator

<b>Product extension optional Light source</b>	No
--	----

### Display

<b>Number of LEDs</b>	4
-----------------------	---

### General technical data

<b>Insulation voltage</b>	
• rated value	30 V
<b>Degree of pollution</b>	3
<b>Type of voltage</b>	
• of the operating voltage	DC
• of the input voltage	DC
<b>Surge voltage resistance rated value</b>	0.8 kV
<b>Consumed current</b>	
• maximum	49 mA
<b>Protection class IP</b>	IP20
<b>Reference code acc. to DIN EN 81346-2</b>	P
<b>Reference code acc. to DIN EN 61346-2</b>	P
<b>Operating voltage</b>	
• rated value	18 ... 30 V
• at DC	
— rated value	24 V
<b>Operating voltage 1</b>	
• at DC rated value	24 V

### Communication/ Protocol



<b>Protocol is supported</b>	
• IO-Link protocol	Yes
<b>IO-Link transfer rate</b>	COM2 (38,4 kBaud)
<b>Point-to-point cycle time between master and IO-Link device minimum</b>	10 ms

<b>Type of voltage supply via input/output link master</b>	Yes
<b>Amount of data</b>	
<ul style="list-style-type: none"> <li>• of the address area of the inputs with cyclical transfer total</li> </ul>	2 byte
<ul style="list-style-type: none"> <li>• of the address area of the outputs with cyclical transfer total</li> </ul>	0 byte
<b>Auxiliary circuit</b>	
<b>Number of NC contacts for auxiliary contacts</b>	0
<b>Number of NO contacts for auxiliary contacts</b>	5
<b>Inputs/ Outputs</b>	
<b>Number of digital inputs</b>	0
<ul style="list-style-type: none"> <li>• safety-related</li> </ul>	0
<b>Number of digital outputs</b>	5
<b>Output voltage at digital output at DC rated value</b>	23.5 V
<b>Output current per output</b>	250 mA
<b>Connections/ Terminals</b>	
<b>Type of electrical connection</b>	screw-type terminals
<b>Type of connectable conductor cross-sections</b>	
<ul style="list-style-type: none"> <li>• solid with core end processing</li> </ul>	1x (0.2 ... 2.5 mm <sup>2</sup> ), 2x (0.2 ... 0.75 mm <sup>2</sup> )
<ul style="list-style-type: none"> <li>• solid without core end processing</li> </ul>	1x (0.2 ... 2.5 mm <sup>2</sup> ), 2x (0.2 ... 0.75 mm <sup>2</sup> )
<ul style="list-style-type: none"> <li>• finely stranded with core end processing</li> </ul>	1x (0.2 ... 2.5 mm <sup>2</sup> ), 2x (0.25 ... 0.75 mm <sup>2</sup> )
<ul style="list-style-type: none"> <li>• finely stranded without core end processing</li> </ul>	1x (0.2 ... 2.5 mm <sup>2</sup> ), 2x (0.2 ... 0.75 mm <sup>2</sup> )
<ul style="list-style-type: none"> <li>• at AWG conductors</li> </ul>	1x (24 ... 14), 2x (24 ... 19)
<b>Tightening torque</b>	
<ul style="list-style-type: none"> <li>• with screw-type terminals</li> </ul>	0.35 ... 0.4 N·m
<b>Product Function</b>	
<b>Product function parameterizable</b>	Yes
<b>Safety related data</b>	
<b>MTBF</b>	
<ul style="list-style-type: none"> <li>• at 70 °C</li> </ul>	138 y
<ul style="list-style-type: none"> <li>• at full load at 25 °C</li> </ul>	141 y
<b>Protection against electrical shock</b>	finger-safe
<b>Ambient conditions</b>	
<b>Ambient temperature</b>	
<ul style="list-style-type: none"> <li>• during operation</li> </ul>	-25 ... +70 °C
<ul style="list-style-type: none"> <li>• during storage</li> </ul>	-40 ... +80 °C
Environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95 %, no condensation in operation permitted)
<b>Installation/ mounting/ dimensions</b>	
<b>Mounting type</b>	front panel mounting

• of modules and accessories	Front plate mounting
<b>Height</b>	36 mm
<b>Width</b>	50 mm
<b>Depth</b>	36.4 mm
<b>Required spacing</b>	
• with side-by-side mounting	
— forwards	100 mm
— Backwards	100 mm
— upwards	100 mm
— downwards	100 mm
— at the side	100 mm

Measuring circuit	
<b>Product function</b>	IO-Link 24 V DC

### Certificates/ approvals

General Product Approval	Declaration of Conformity	Test Certificates	other
	 EG-Konf.	<a href="#">Miscellaneous</a> <a href="#">Type Test Certificates/Test Report</a>	<a href="#">Special Test Certificate</a> <a href="#">Confirmation</a>

### Further information

- Information- and Downloadcenter (Catalogs, Brochures,...)**  
<https://www.siemens.com/ic10>
- Industry Mall (Online ordering system)**  
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-1GE10-1AA0>
- Cax online generator**  
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-1GE10-1AA0>
- Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**  
<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1GE10-1AA0>
- Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1400-1GE10-1AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-1GE10-1AA0&lang=en)

last modified: 03/06/2020