

SIRIUS ACT with PROFINET: Standard interface module 24 V DC, spring-type terminal, Front plate mounting 1 to 20 terminal modules connectable



Product brand name	SIRIUS ACT
Product designation	Interface module for PROFINET
Product type designation	3SU1

Display

Display version <ul style="list-style-type: none"> • for diagnostic function: Supply voltage monitoring Power LED • status Tx/Rx link 	<p>Yes</p> <p>Yes</p>
--	-----------------------

General technical data

Product function <ul style="list-style-type: none"> • Reverse polarity protection • Diagnostics function • Alarms • I&M data 	<p>Yes</p> <p>Yes</p> <p>Yes</p> <p>Yes; I&M0 ... I&M3</p>
Firmware version	1.0.0
Hardware version	1
Configuration function with dataset	Yes
Software version with STEP 7 in the TIA Portal required	Integrated in TIA Portal Version 14 SP1 or higher (HSP for V13 and V14)

Number of units per rack maximum	20
Number of submodules per station maximum	24
Power loss [W] typical	0.67 W
Insulation voltage rated value	30 V
Degree of pollution	3
Type of voltage	
• of the operating voltage	DC
• of the input voltage	DC
Surge voltage resistance rated value	0.8 kV
Consumed current	
• maximum	100 mA
• Rated value	28 mA
Protection class IP	IP20
Reference code acc. to DIN EN 81346-2	K
Operating voltage rated value	20.4 V
I²t value	0.008 A ² ·s

Supply voltage	
Supply voltage at DC Rated value	24 V

Communication/ Protocol	
Protocol is supported	
• PROFINET IO protocol	Yes
• PROFI-safe protocol	No
Product function at the Ethernet interface	
• Autocrossover	Yes
• Autonegotiation	Yes
Protocol at the 1st interface	
• media redundancy protocol	No
Product function at the 1st interface	
• PROFINET IO device	Yes
Product function of the PROFINET IO device is supported PROFINET system redundancy (S2)	No
Service as PROFINET IO device	
• prioritized startup	No
• isochronous mode	No
• supports Shared Device	No
• supports PROFINET energy	No
• IRT	No
• MRP	No
• MRPD	No
Service for open IE communication	
• LLDP	Yes
• SNMP	Yes

• TCP/IP	Yes
GSD version/revision with PROFINET required	V2.3
Transmission mode for Industrial Ethernet	PROFINET with 100 Mbps full duplex (100BASE-TX)
Network load class acc. to PROFINET	1
Specification for Security Level 1 test acc. to PROFINET	Resilient to network loading

Control circuit/ Control	
Inrush current maximum	16 A

Galvanic isolation	
Galvanic isolation between PROFINET and all other circuits	Yes

Inputs/ Outputs	
Number of digital inputs	0
• safety-related	0
Number of digital outputs	0

Connections/ Terminals	
Type of electrical connection	spring-loaded terminals
Connectable conductor cross-section for auxiliary contacts	
• single or multi-stranded	0.2 ... 2.5 mm ²
• finely stranded with core end processing	2.5 mm ²
Connectable conductor cross-section	
• solid	0.2 ... 2.5 mm ²
• solid with core end processing	0.2 ... 2.5 mm ²
• finely stranded with core end processing	0.25 ... 2.5 mm ²
• finely stranded without core end processing	0.2 ... 2.5 mm ²
AWG number as coded connectable conductor cross section	30 ... 12
Tightening torque with screw-type terminals	0.5 ... 0.6 N·m

Safety related data	
Service life maximum	20 y
Design of the interface	
• Ethernet interface	Yes; for Ethernet services
• Fast Ethernet interface	Yes; PROFINET with 100 Mbps
Interface design 1	
• integrated switch	No
• RJ45 (Ethernet)	Yes
Number of ports at the 1st interface	1
Number of interfaces acc. to PROFINET	1




Ambient conditions	
---------------------------	--

Environmental category during operation acc. to IEC 60721	3M6, 3S2, 3B2, 3K6 (with relative air humidity of 10 ... 95 %, no condensation in operation permitted)
Explosion protection marking for intrinsic safety of related equipment EEx ia	No
Explosion protection marking for intrinsic safety of related equipment EEx ib	No

Installation/ mounting/ dimensions

Mounting type of modules and accessories	Front plate mounting
Height	80.1 mm
Width	40 mm
Depth	72.1 mm

Certificates/ approvals

General Product Approval	Declaration of Conformity	Test Certificates
 UL	 EAC	 EG-Konf.
	Miscellaneous	Type Test Certificates/Test Report
		Special Test Certificate

other

[Confirmation](#)
[PROFINET-Certification](#)
[PROFIsafe-Certification](#)



Profibus

Further information



Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>


Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-1LK10-3AA1>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-1LK10-3AA1>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-1LK10-3AA1>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-1LK10-3AA1&lang=en





last modified:

03/08/2020