



Powering Business Worldwide

pe.eaton.com

M22 Contact Block

M22-K10

M22-K10

UPC: 786685278001

Dimensions: 1.46 IN * 1.18 IN * 1.03 IN (L * W * H)

Notes: All NC contact blocks are positively driven contact.

Warranty: Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.

Specifications:

- Special Features:** NC contact blocks are positively driven
- Type:** Contact Block
- Actuator:** Front, Screw
- Button Color:** Black
- Contact Configuration:** NO
- Environmental Rating:** IP66, NEMA 4X, 13
- Size:** 22.5 mm
- Series:** M22

Supporting documents:

- [Eatons Volume 7-Logic Control, Operator Interface and Connectivity Solutions Catalog](#)
- [M22-K 3D Inventor Drawing](#)
- [M22-K 3D Model Xchange Drawing](#)
- [Drawing Dataset Drawing](#)
- [M22-K AutoCAD 2D Footprint \(mm\) Drawing](#)
- [M22-K AutoCAD 2D Footprint Drawing](#)
- [M22-K 2D Drawing Xchange Drawing](#)
- [M22-K 2D PDF Drawing](#)
- [M22 Operators and Accessories Inst Leaflet](#)
- [M22 Pilot Devices Product Aid](#)
- [Quick Selector - M22 Pushbuttons Specification](#)



Certifications:

- Lloyd's Register Certified
- CCC Marked
- CSA Certified

Product compliance:

- CE Marked
- Bureau Veritas
- GoST-R

© 2016 Eaton. All rights reserved.