



Powering Business Worldwide

pe.eaton.com

## Contactor Accessory - Auxiliary Contact

XTCEXFAC20

XTCEXFAC20

UPC: 786689004958

**Dimensions:** x \* x \* x (L \* W \* H)

**Notes:** Interlocked opposing contacts, to IEC/EN 60947-5-1 Annex L (positively driven), within the auxiliary contact modules (not NOE and NCL contacts) and between the auxiliary contacts and built-in contacts of the XTRE control relays.

**Warranty:** No Data

### Specifications:

- Mounting:** Front
- Type:** Contactor Accessory - Auxiliary Contact
- Used With:** XTRE control relays
- Conventional Thermal Current:** 16A
- Contact Configuration:** 2NO
- Number Of Poles:** Two-pole
- Quantity:** 5
- Rated Operational Current:** 6A at 220/230/240V; 3A at 380/400/415V; 1.5A at 500V
- Terminals:** Screw terminals

### Supporting documents:

- [Eatons Volume 5-Motor Control and Protection Catalog](#)

### Certifications:

- IEC 60947
- UL Listed
- EN 60947
- CSA Certified

### Product compliance:

- CCC Marked



- CE Marked
- ATEX Compliant

---

© 2016 Eaton. All rights reserved.