



**TECHNICAL CHARACTERISTICS
CARATTERISTICHE TECNICHE**

Stripping length Spellatura filo	8 mm
Ø A Ø A	1.3
Rated Current Corrente Nominale	10A
Wire section Sezione filo	0.75 mm ²
Material and surface of the contact Materiale e finitura del contatto	Copper Alloy / Gold plated Legia di rame / Dorati
Wire section Calibro filo	16 AVG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: --- DRWN: --- CHK'D: --- REV: --- APPR: ---	QUALITY SYMBOLS	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)	DIMENSION UNITS MM	SCALE 3:1	molex			
	▽ = 0	Dim. Tol.	DRWN BY ELONGHI	DATE 07/02/2014				7100.4203.1 10A turned crimp female contact for inserts and modules
	▽ = 0	0,5+3 ± 0,05	CHK'D BY ---	DATE ---	PRODUCT CUSTOMER DRAWING			
	▽ = 0	3+6 ± 0,05	APPR BY ---	DATE ---				SERIES 09360
	▽ = 0	6+30 ± 0,1	ANGULAR DIMENSIONS	DRAWING SIZE A4	FIRST ANGLE PROJECTION	DOCUMENT NUMBER 0936010044	DOC TYPE PSD	DOC PART 000