



**TECHNICAL CHARACTERISTICS
CARATTERISTICHE TECNICHE**

Stripping length Spellatura filo	8 mm
Ø A Ø A	1.45
Rated Current Corrente Nominale	10A
Wire section Sezione filo	1.0 mm ²
Material and surface of the contact Materiale e finitura del contatto	Copper Alloy / Hard silver plated Legga di rame / Argentati
Wire section Calibro filo	18 AVG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: --- DRWN: --- CHK'D: --- REV: --- APP'R: ---	QUALITY SYMBOLS	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)	DIMENSION UNITS MM	SCALE 3:1	molex			
	▽ = 0	Dim. Tol.	DRWN BY ELONGHI	DATE 07/02/2014				7100.4214.0 10A turned crimp male contact for inserts and modules
	▽ = 0	3+6 ± 0.05	CHK'D BY ---	DATE ---	PRODUCT CUSTOMER DRAWING			
	▽ = 0	6+30 ± 0.1	APPR BY ---	DATE ---				SERIES 09360
	▽ = 0	30+120 ± 0.15	ANGULAR DIMENSIONS	DRAWING SIZE A4	FIRST ANGLE PROJECTION	DOCUMENT NUMBER 0936010057	DOC TYPE PSD	DOC PART 000