



**TECHNICAL CHARACTERISTICS
CARATTERISTICHE TECNICHE**

Stripping length Spellatura filo	6 mm
Rated Current Corrente Nominale	10A
Wire section Sezione filo	2.5 mm ²
Material and surface of the contact Materiale e finitura del contatto	Copper Alloy / Silver plated Legga di rame / Argentati
Wire section Calibro filo	14 AWG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: DRWN: CHKD: REV	QUALITY SYMBOLS	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)	DIMENSION UNITS MM	SCALE 4:1			
	▽ = 0	Dim. Tol.	DRWN BY ELONGHI	DATE 10/02/2014		7100.4216.0 10A TURNED CRIMP MALE CONTACT Contatto maschio 10A a crimpare tornito	
	▽ = 0	3+6 ± 0.05	CHKD BY MDUGO	DATE 10/02/2014	PRODUCT CUSTOMER DRAWING		
	▽ = 0	6+30 ± 0.1	APPR BY MDUGO	DATE 10/02/2014		SERIES 93601	
	▽ = 0	30+120 ± 0.15	DRAWING SIZE A4	FIRST ANGLE PROJECTION	MATERIAL NUMBER 936010061	CUSTOMER SALES DRAWING	
▽ = 0	120+400 ± 0.2	ANGULAR DIMENSIONS		DOCUMENT NUMBER 936010061	DOC TYPE PSD	DOC PART 000	SHEET NUMBER 1 OF 1
▽ = 0	10+50 ± 0°30'	<10 ± 1°					
▽ = 0	6+30 ± 0.1	10+50 ± 0°30'					
▽ = 0	30+120 ± 0.15	50+120 ± 0°20'					
▽ = 0	120+400 ± 0.2	120+400 ± 0°10'					