



TECHNICAL CHARACTERISTICS CARATTERISTICHE TECNICHE	
N° of grooves Num.gole	0
Rated Current Corrente Nominale	16A
Wire section Sezione filo	0.5 mm <sup>2</sup>
Material and surface of the contact Materiale e finitura del contatto	Copper Alloy / Silver plated Legga di rame / Argentati
Wire section Calibro filo	20 AWG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION	QUALITY SYMBOLS	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)		DIMENSION UNITS	SCALE				
		Dim.	Tol.	MM	4:1				
EC NO:     DRWN:     CHK'D:     APPR:     REV:	▽ = 0	Dim.	Tol.	DRWN BY	DATE	7300.6241.0 16A CRIMP FEM CONTACT 0.5mm <sup>2</sup> SILVER			
	▽ = 0	0.5+3	± 0.05	ELONGHI	10/02/2014				
	▽ = 0	3+6	± 0.05	CHK'D BY	DATE	PRODUCT CUSTOMER DRAWING			
	▽ = 0	6+30	± 0.1	MDUGO	10/02/2014				
	▽ = 0	30+120	± 0.15	APPR BY	DATE	SERIES	MATERIAL NUMBER	CUSTOMER	
	▽ = 0	120+400	± 0.2	MDUGO	10/02/2014	93601	0936010173	GENERAL MARKET	
	▽ = 0	ANGULAR DIMENSIONS		DRAWING SIZE	FIRST ANGLE PROJECTION	DOCUMENT NUMBER	DOC TYPE	DOC PART	SHEET NUMBER
	▽ = 0	<10	± 1°	A4		0936010173	PSD	000	1 OF 1
	▽ = 0	10+50	± 0°30'						
	▽ = 0	50+120	± 0°20'						
▽ = 0	120+400	± 0°10'							