



**TECHNICAL CHARACTERISTICS
CARATTERISTICHE TECNICHE**

Stripping length Spellatura filo	7.5 mm
Rated Current Corrente Nominale	16A
Wire section Sezione filo	2.5 mm ²
Material and surface of the contact Materiale e finitura del contatto	Copper Alloy / Gold plated Legga di rame / Dorati
Wire section Calibro filo	14 AWG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: --- DRWN: ELONGHI CHK'D: AMELZI REV APPR: AMELZI	03/03/2014 03/03/2014	QUALITY SYMBOLS ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)		DIMENSION UNITS MM	SCALE 2:1	molex			
			Dim.	Tol.	DRWN BY ELONGHI	DATE 26/10/2016				
			3+6	± 0.05	CHK'D BY AMELZI	DATE 26/10/2016	7300.6248.1 16A TURNED CRIMP MALE CONTACT Contatto maschio 16A a crimpare tornito			
			6+30	± 0.1	APPR BY AMELZI	DATE 26/10/2016				
		30+120	± 0.15	ANGULAR DIMENSIONS		PRODUCT CUSTOMER DRAWING				
		120+400	± 0.2	<10	± 1°	SERIES 93601				
		10+50	± 0°30'	120+400	± 0°10'	DRAWING SIZE A4	FIRST ANGLE PROJECTION	MATERIAL NUMBER 936010188		
		50+120	± 0°20'			CUSTOMER GENERAL MARKET				
		120+400	± 0°10'			DOCUMENT NUMBER 936010188		DOC TYPE PSD	DOC PART 000	SHEET NUMBER 1 OF 1