



**TECHNICAL CHARACTERISTICS
CARATTERISTICHE TECNICHE**

Stripping length Spellatura filo	9.6 mm
Rated Current Corrente Nominale	40A
Wire section Sezione filo	6.0 mm ²
Material and surface of the contact Materiale e finitura del contatto	Copper Alloy / Silver plated Legna di rame / Argentati
Wire section Calibro filo	7 AWG

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: --- DRWN: ELONGHI 03/03/2014 CHK'D: AMELZI 03/03/2014 REV APPR: AMELZI 03/03/2014	QUALITY SYMBOLS	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)	DIMENSION UNITS MM	SCALE 3:1		
	▽ = 0	Dim. Tol.	DRWN BY ELONGHI	DATE 03/03/2014		7600.5703.0 40A TURNED CRIMP MALE CONTACT Contatto maschio 40A a crimpare tornito
	▽ = 0	0.5+3 ± 0.05	CHK'D BY AMELZI	DATE 03/03/2014		
	▽ = 0	3+6 ± 0.05	ANGULAR DIMENSIONS	APPR BY AMELZI	DATE 03/03/2014	PRODUCT CUSTOMER DRAWING
	▽ = 0	6+30 ± 0.1	<10 ± 1°	DRAWING SIZE A4	FIRST ANGLE PROJECTION	SERIES 93601
▽ = 0	30+120 ± 0.15	10+50 ± 0°30'			MATERIAL NUMBER 936010412	
▽ = 0	120+400 ± 0.2	50+120 ± 0°20'			CUSTOMER GENERAL MARKET	
▽ = 0		120+400 ± 0°10'			DOCUMENT NUMBER 936010412	
					DOC TYPE PSD	
					DOC PART 000	
					SHEET NUMBER 1 OF 1	