



TECHNICAL CHARACTERISTICS

Size	16B 77x27
Enclosure Type	STD for inserts up to 500V
Enclosure Body	Die Cast Aluminium
Surface Finishing	Polyester Powder Coating
Protection Class EN 60529	IP66/IP69
Thread	/

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: --- DRWN: --- CHK'D: --- APPR: --- REV: ---	QUALITY SYMBOLS ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0 ▽ = 0	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED) Dim. Tol. 0.5+3 ± 0.05 3+6 ± 0.05 6+30 ± 0.1 30+120 ± 0.15 120+400 ± 0.2 ANGULAR DIMENSIONS <10 ± 1° 10+50 ± 0°30' 50+120 ± 0°20' 120+400 ± 0°10'	DIMENSION UNITS MM	SCALE 1:1	molex 7816.6405.0 Bulkhead Mounting Housing 1 Lever	
	DRWN BY ELONGHI	DATE 10/04/2017	CHK'D BY AMELZI	DATE 10/04/2017		APPR BY AMELZI
	DRAWING SIZE A3	FIRST ANGLE PROJECTION	SERIES 09360	MATERIAL NUMBER 0936012571	CUSTOMER GENERAL MARKET	PRODUCT CUSTOMER DRAWING
	DOCUMENT NUMBER 0936012571	DOC TYPE PSD	DOC PART 000	SHEET NUMBER 1 OF 1		