



TECHNICAL CHARACTERISTICS
CARATTERISTICHE TECNICHE

Size <i>Grandezza</i>	24B 104x27
Type of enclosure <i>Tipo di custodia</i>	STD for inserts up to 500V <i>per inserti fino a 500V</i>
Material body <i>Materiale del corpo</i>	Die cast aluminium alloy <i>Lega di alluminio pressofusa</i>
Finishing Surface <i>Finitura superficiale</i>	Polyester powder coating <i>Verniciatura a polvere poliestere</i>
Protection class EN 60529 <i>Grado di protezione EN 60529</i>	IP66/IP69
Entries <i>Ingressi</i>	M25

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

EC DESCRIPTION EC NO: DRWN: CHKD: APPR: REV	QUALITY SYMBOLS	GENERAL TOLERANCES ISO 2768-2/F (UNLESS SPECIFIED)	DIMENSION UNITS MM	SCALE 1:1	molex			
	▽ = 0	Dim. Tol.	DRWN BY ELONGHI	DATE 24/01/2014				7824.6573.0 24B STD HOOD 4PGS LC S/E M25
	▽ = 0	0.5+3 ± 0.05	CHK'D BY AMELZI	DATE 24/01/2014	PRODUCT CUSTOMER DRAWING			
	▽ = 0	3+6 ± 0.05 6+30 ± 0.1	APPR BY AMELZI	DATE 24/01/2014				SERIES 09360
	▽ = 0	30+120 ± 0.15 120+400 ± 0.2	ANGULAR DIMENSIONS	DRAWING SIZE A3	FIRST ANGLE PROJECTION	DOCUMENT NUMBER 0936013770	DOC TYPE PSD	DOC PART 000