




Model Number

NMB1,5-8GM50-E2-C-FE-V1


Features

- Stainless steel sensing face
- 1.5 mm flush
- 3-wire DC
- Weld field immune
- Weld slag resistant coating
- Ferrous targets

Connection



Pinout




Wire colors in accordance with EN 60947-5-2

1	BN	(brown)
2	WH	(white)
3	BU	(blue)
4	BK	(black)

Accessories

- BF 8**
Mounting flange, 8 mm
- V1-G-OR2M-POC**
Female cordset, M12, 4-pin, TPE cable, welding-bead resistant
- V1-W-OR2M-POC**
Female cordset, M12, 4-pin, TPE cable, welding-bead resistant

Dimensions



Technical Data

General specifications			
Switching element function		PNP	NO
Rated operating distance	s_n	1.5 mm	
Installation		flush	
Output polarity		DC	
Assured operating distance	s_a	0 ... 1.215 mm	
Actuating element		Ferrous targets	
Reduction factor r_{Al}		0	
Reduction factor r_{Cu}		0	
Reduction factor r_{304}		0.6	
Reduction factor r_{St37}		1	
Reduction factor r_{Brass}		0	

Nominal ratings			
Operating voltage	U_B	10 ... 30 V DC	
Switching frequency	f	0 ... 5 Hz	
Hysteresis	H	5 ... 15 typ. 10 %	
Reverse polarity protection		reverse polarity protected	
Short-circuit protection		pulsing	
Voltage drop	U_d	≤ 2 V	
Operating current	I_L	0 ... 100 mA	
Current consumption		≤ 10 mA	
Off-state current	I_r	≤ 10 μ A	
Switching state indication		LED, red	
Mag. Field strength, AC fields		250 mT	
Mag. Field strength, DC fields		250 mT	

Ambient conditions	
Ambient temperature	-25 ... 75 °C (-13 ... 167 °F)

Mechanical specifications	
Connection type	Device connector M12 x 1 , 4-pin
Housing material	stainless steel 1.4305 / AISI 303, black PTFE coated
Sensing face	stainless steel 1.4305 / AISI 303, black PTFE coated
Protection degree	IP67

Compliance with standards and directives	
Standard conformity	
Standards	EN 60947-5-2:2007 IEC 60947-5-2:2007

Approvals and certificates	
UL approval	cULus Listed, General Purpose
CSA approval	cCSAus Listed, General Purpose
CCC approval	Products with a maximum operating voltage of ≤ 36 V do not bear a CCC marking because they do not require approval.

Release date: 2013-01-25 13:08 Date of issue: 2013-01-25 904963_eng.xml