





LED module, green, 110-230 V AC

General technical data	
Display version LED	Yes
Protection class IP	IP00
Design of the switching function positively driven	No
Reference code acc. to DIN EN 81346-2	P
Control circuit/ Control	
Control supply voltage at AC	
<ul style="list-style-type: none"> at 50 Hz rated value at 60 Hz rated value 	110 ... 230 V
Control supply voltage frequency	
<ul style="list-style-type: none"> 1 rated value 2 rated value 	50 Hz 60 Hz
Supply voltage frequency for auxiliary and control current circuit rated value	50 ... 60 Hz
Product component Plug-in socket	No
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts	
<ul style="list-style-type: none"> for auxiliary contacts 	0
Main circuit	
Type of voltage	AC
Display	
Display version	
<ul style="list-style-type: none"> as status display by LED 	LED green
Connections/ Terminals	
Product function	
<ul style="list-style-type: none"> removable terminal 	No
Installation/ mounting/ dimensions	
Mounting position	any
Width	15.5 mm
Certificates/ approvals	

General Product Approval		Declaration of Conformity		other	
				Miscellaneous	Confirmation
UL	VDE		EG-Konf.		

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mfb=LZS:PTMG0730>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mfb=LZS:PTMG0730>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PTMG0730>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mfb=LZS:PTMG0730&lang=en

last modified:

04/04/2020