

LED module, red for plug-in relay, PT and RT series, 110-230 V AC without freewheeling diode



Figure similar

General technical data	
Display version LED	Yes
Protection class IP	IP00
Design of the switching function positively driven	No
Reference code acc. to DIN EN 81346-2	P
Control circuit/ Control	
Control supply voltage at AC	
<ul style="list-style-type: none"> at 50 Hz rated value at 60 Hz rated value 	110 ... 230 V
Control supply voltage frequency	
<ul style="list-style-type: none"> 1 rated value 2 rated value 	50 Hz 60 Hz
Supply voltage frequency for auxiliary and control current circuit rated value	50 ... 60 Hz
Product component Plug-in socket	No
Auxiliary circuit	
Number of NC contacts for auxiliary contacts	0

Number of NO contacts for auxiliary contacts	0
Number of CO contacts	
• for auxiliary contacts	0

Main circuit

Type of voltage	AC
-----------------	----

Display

Display version	
• as status display by LED	LED red





Connections/ Terminals

Product function	
• removable terminal	No

Installation/ mounting/ dimensions

Mounting position	any
Width	15.5 mm

Certificates/ approvals

General Product Approval		Declaration of Conformity		other
				Miscellaneous Confirmation
UL	VDE		EG-Konf.	

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)
<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)
<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZS:PTML0730>

Cax online generator
<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:PTML0730>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)
<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PTML0730>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)
http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:PTML0730&lang=en

last modified: 04/04/2020