

Freewheeling diode with connection to A1 6-230 V DC

### General technical data

Display version LED	No
Protection class IP	IP00
Design of the switching function positively driven	No
Reference code acc. to DIN EN 81346-2	R

### Control circuit/ Control

Control supply voltage at DC	6 ... 230 V
• rated value	
Product component Plug-in socket	No

### Auxiliary circuit

Number of NC contacts for auxiliary contacts	0
Number of NO contacts for auxiliary contacts	0
Number of CO contacts	0
• for auxiliary contacts	

### Main circuit

Type of voltage	DC
-----------------	----





### Connections/ Terminals

Product function	No
• removable terminal	

### Installation/ mounting/ dimensions

Mounting position	any
Width	15.5 mm

### Certificates/ approvals

General Product Approval		Declaration of Conformity		other
				<a href="#">Miscellaneous</a> <a href="#">Confirmation</a>
UL	VDE		EG-Konf.	

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=LZS:PTMT00A0>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=LZS:PTMT00A0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/LZS:PTMT00A0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=LZS:PTMT00A0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=LZS:PTMT00A0&lang=en)

last modified:

04/02/2020