

Cable Ties

Stainless Steel, Self-Locking



Technical Data

Material: Best 316 / 304 Grade Stainless Steel
 Temperature Range: -80°F to +538°F
 Colors: Natural

Part No.	Length (in)	Length (mm)	Width (in)	Max Bundle Ø (in)	Tensile Strength (lbs)	Tensile Strength (kgs)
TY-4"-222-SS	4.0	100	0.181	0.866		
TY-6"-222-SS	6.0	150	0.181	1.378		
TY-8"-222-SS	8.0	200	0.181	1.967		
TY-10"-222-SS	10.0	250	0.181	2.559		
TY-12"-222-SS	12.0	300	0.181	3.228		
TY-14"-222-SS	14.0	350	0.181	3.543		
TY-16"-222-SS	16.0	400	0.181	4.134		
TY-18"-222-SS	18.0	450	0.181	5.118		
TY-20"-222-SS	20.0	500	0.181	5.512		
TY-22"-222-SS	22.0	550	0.181	6.378		
TY-24"-222-SS	24.0	600	0.181	7.283		
TY-26"-222-SS	26.0	650	0.181	7.480		
TY-28"-222-SS	28.0	700	0.181	8.071		
TY-30"-222-SS	30.0	750	0.181	8.780		
TY-32"-222-SS	32.0	800	0.181	9.252		
TY-34"-222-SS	34.0	850	0.181	9.843		
TY-36"-222-SS	36.0	900	0.181	10.236		
TY-38"-222-SS	38.0	950	0.181	10.709		
TY-40"-222-SS	40.0	1,000	0.181	11.417		
TY-42"-222-SS	42.0	1,050	0.181	11.811		
TY-44"-222-SS	44.0	1,100	0.181	12.205		
TY-46"-222-SS	46.0	1,150	0.181	12.598		
<hr/>						
TY-6"-355-SS	6.0	150	0.311	1.378		
TY-8"-355-SS	8.0	200	0.311	1.967		
TY-10"-355-SS	10.0	250	0.311	2.559		
TY-12"-355-SS	12.0	300	0.311	3.228		
TY-14"-355-SS	14.0	350	0.311	3.543		
TY-16"-355-SS	16.0	400	0.311	4.134		
TY-18"-355-SS	18.0	450	0.311	5.118		
TY-20"-355-SS	20.0	500	0.311	5.512		
TY-22"-355-SS	22.0	550	0.311	6.378		
TY-24"-355-SS	24.0	600	0.311	7.283		
TY-26"-355-SS	26.0	650	0.311	7.480		
TY-28"-355-SS	28.0	700	0.311	8.071		
TY-30"-355-SS	30.0	750	0.311	8.780		
TY-32"-355-SS	32.0	800	0.311	9.252		
TY-34"-355-SS	34.0	850	0.311	9.843		
TY-36"-355-SS	36.0	900	0.311	10.236		
TY-38"-355-SS	38.0	950	0.311	10.709		
TY-40"-355-SS	40.0	1,000	0.311	11.417		
TY-42"-355-SS	42.0	1,050	0.311	11.811		
TY-44"-355-SS	44.0	1,100	0.311	12.205		
TY-46"-355-SS	46.0	1,150	0.311	12.598		

• standard stock item

222 lbs,
100 kgs

355 lbs,
161 kgs

Cable Ties

Nylon, Self-Locking



Technical Data

Material: Best Nylon 6/6 Certified by UL
 Temperature Range: -40°F to +185°F
 Colors: Natural, UV Black (standard stock)
 Other colors available on request



Part No.	Color (XXX)	Length (in)	Length (mm)	Width (in)	Max Bundle Ø (in)	Tensile Strength (lbs)	Tensile Strength (kgs)
TY-2"-18-XXX	BLK, CLR	2.4	60	0.098	0.433		
TY-3"-18-XXX	BLK, CLR	3.2	80	0.098	0.630		
TY-4"-18-XXX	BLK, CLR	4.0	100	0.098	0.866		
TY-5"-18-XXX	BLK, CLR	4.8	120	0.098	1.181		
TY-6"-18-XXX	BLK, CLR	6.0	150	0.098	1.378		
TY-7"-18-XXX	BLK, CLR	6.5	160	0.098	1.575		
TY-8"-18-XXX	BLK, CLR	8.0	200	0.098	1.575		
<hr/>							
TY-5"-40-XXX	BLK, CLR	4.8	120	0.138	1.181		
TY-6"-40-XXX	BLK, CLR	6.0	150	0.138	1.378		
TY-7"-40-XXX	BLK, CLR	7.2	180	0.138	1.654		
TY-8"-40-XXX	BLK, CLR	8.0	200	0.138	1.969		
TY-10"-40-XXX	BLK, CLR	10.0	250	0.138	2.559		
TY-11"-40-XXX	BLK, CLR	11.2	280	0.138	2.756		
TY-12"-40-XXX	BLK, CLR	12.0	300	0.138	3.150		
TY-15"-40-XXX	BLK, CLR	14.8	370	0.138	4.016		
<hr/>							
TY-5"-50-XXX	BLK, CLR	4.8	120	0.181	0.945		
TY-6"-50-XXX	BLK, CLR	6.0	150	0.181	1.378		
TY-7"-50-XXX	BLK, CLR	7.6	190	0.181	1.811		
TY-8"-50-XXX	BLK, CLR	8.0	200	0.181	1.969		
TY-10"-50-XXX	BLK, CLR	10.0	250	0.181	2.559		
TY-11"-50-XXX	BLK, CLR	11.2	280	0.181	2.756		
TY-12"-50-XXX	BLK, CLR	12.0	300	0.181	3.228		
TY-14"-50-XXX	BLK, CLR	14.0	350	0.181	3.543		
TY-15"-50-XXX	BLK, CLR	14.8	370	0.181	4.016		
TY-16"-50-XXX	BLK, CLR	16.0	400	0.181	4.134		
TY-17"-50-XXX	BLK, CLR	17.2	430	0.181	4.724		
TY-18"-50-XXX	BLK, CLR	18.0	450	0.181	5.118		
TY-20"-50-XXX	BLK, CLR	20.0	500	0.181	5.512		
TY-21"-50-XXX	BLK, CLR	21.2	530	0.181	5.787		
<hr/>							
TY-10"-90-XXX	BLK, CLR	10.0	250	0.268	2.559		
TY-12"-90-XXX	BLK, CLR	12.0	300	0.268	3.150		
TY-14"-90-XXX	BLK, CLR	14.8	370	0.268	4.016		
<hr/>							
TY-6"-120-XXX	BLK, CLR	6.0	150	0.283	1.299		
TY-8"-120-XXX	BLK, CLR	8.0	200	0.283	1.969		
TY-10"-120-XXX	BLK, CLR	10.0	250	0.299	2.480		
TY-12"-120-XXX	BLK, CLR	12.0	300	0.299	3.228		
TY-14"-120-XXX	BLK, CLR	14.0	350	0.299	3.543		
TY-15"-120-XXX	BLK, CLR	14.8	370	0.299	4.016		
TY-16"-120-XXX	BLK, CLR	16.0	400	0.299	4.134		
TY-18"-120-XXX	BLK, CLR	18.0	450	0.299	4.646		
TY-20"-120-XXX	BLK, CLR	20.0	500	0.299	5.906		
TY-22"-120-XXX	BLK, CLR	22.0	550	0.299	6.299		
<hr/>							
TY-17"-175-XXX	BLK, CLR	17.2	430	0.346	4.409		
TY-22"-175-XXX	BLK, CLR	22.0	550	0.346	6.299		
TY-24"-175-XXX	BLK, CLR	24.0	600	0.346	6.693		
TY-26"-175-XXX	BLK, CLR	26.0	650	0.346	7.480		
TY-28"-175-XXX	BLK, CLR	28.0	700	0.346	8.071		
TY-30"-175-XXX	BLK, CLR	30.4	760	0.346	8.858		
TY-32"-175-XXX	BLK, CLR	32.4	810	0.346	9.409		
TY-36"-175-XXX	BLK, CLR	36.8	920	0.346	10.433		
TY-45"-175-XXX	BLK, CLR	45.7	1,168	0.346	14.173		

• standard stock item